

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, SEIJI TAKAHASHI, a citizen of Japan residing at Tokyo, Japan, HIROKI KOBAYASHI, a citizen of Japan residing at Kanagawa, Japan and SAYAKA KOBAYASHI, a citizen of Japan residing at Tokyo, Japan have invented certain new and useful improvements in

INFORMATION PROCESSING APPARATUS AND INFORMATION
PROCESSING METHOD

of which the following is a specification:-

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to an information processing apparatus capable of connecting to a terminal through the Internet and including a plurality of Web applications and an information processing method in that terminal type information, language information, and profile information of the terminal can be succeeded while a page transition is conducted by a user of the terminal among the plurality of Web applications, and in that information suitable for the terminal can be provided while maintaining user-friendliness.

2. Description of the Related Art

Recently, the Internet has been widely used by not only a client PC (Personal Computer) but also mobile phone and PDA (Personal Digital Assistant) terminal, and information has been provided in various languages and to various level users. A method for providing information has been diversified.

In order to provide information corresponding to a terminal such as the client PC, the mobile phone, or PDA terminal, Japanese Laid-Open Patent Application No.11-175515 discloses that display contents corresponding to the terminal type of the terminal is generated for HTML data created beforehand. Or, Japanese Laid-Open Patent

Application No.2002-63108 discloses that a gateway server, that intermediates between a Web server for providing information and a terminal for requesting information, deletes unnecessary data and adjusts color attributes of an
5 image with respect to information provided from the Web server in response to the request of the terminal, based on the terminal type of the terminal.

Moreover, Japanese Laid-Open Patent Application No.2002-7095 discloses a data processing apparatus including
10 a Web server function capable of providing information concerning a image forming process. In the data processing apparatus, a user of the terminal can obtain information concerning a device for conducting a image forming process and provided with the data processing apparatus, through the
15 Internet.

Furthermore, Japanese Laid-Open Patent Application No.11-306070 discloses a data succeeding method in that by using information input by the user of the terminal is stored in a predetermined storage area, the information
20 can be succeeded while the user conducts the page transition.

However, the above-mentioned conventional methods have the following problems.

In the Web server having the Web server function capable of providing information concerning the image
25 forming process, in a case in that a state of the image forming

process or a device such as a plotter controlled by the Web server for conducting the image forming process is provided, since the information should be provided timely, HTML data cannot be prepared beforehand. Accordingly, the method
5 disclosed by Japanese Laid-Open Patent Application No.11-175515 cannot be applied in this case. In a case of Japanese Laid-Open Patent Application No.2002-63108, a cost of installing the gateway server and maintenance of the gateway server are required.

10 In the data processing apparatus disclosed by Japanese Laid-Open Patent Application No.2002-7095, it is impossible to provide information suitable for the size of a display screen of the terminal such as the client PC, the mobile phone, and the PDA terminal.

15 Moreover, in the data succeeding method disclosed by Japanese Laid-Open Patent Application No.11-306070, a page for allowing the user to input information concerning the user of the terminal is required and the user is required to explicitly input the information
20 into the page. In addition, it is required to manage the information, which is to be succeeded, for each user. Accordingly, it is impossible to automatically provide information suitable for the size of the display screen.

SUMMARY OF THE INVENTION

It is a general object of the present invention to provide an information processing apparatus and an information processing method in which the above-mentioned
5 problems are eliminated.

A more specific object of the present invention is to provide the information processing apparatus capable of connecting to a terminal through the Internet and including a plurality of Web applications and the information
10 processing method in that terminal type information, language information, and profile information of the terminal can be succeeded while a page transition is conducted by a user of the terminal among the plurality of Web applications, and in that information suitable for the
15 terminal can be provided while maintaining user-friendliness.

The above objects of the present invention are achieved by an information processing apparatus connectable to a terminal through network, the information processing
20 apparatus including: a reference Web information generating part specifying a terminal type of the terminal based on a first request requesting Web information sent from the terminal through the network, and generating reference Web information that includes reference path created by adding
25 terminal type information showing the specified terminal

type to a path indicated in the first request for accessing the Web information and that allows the terminal automatically accesses to the reference path; and a communicating part sending the reference Web information to the terminal as a response with respect to the first request, and receiving a second request for requesting the Web information specified by the reference path.

In the information processing apparatus, the Web information automatically accessing by the reference path from the terminal is generated and provided to the terminal. Accordingly, at a side of the terminal, a user of the terminal is not required to input the terminal type information and it is possible for the terminal to obtain the reference path including the terminal type information from the Web information. Moreover, since the reference path is provided to the terminal before the Web information desired by the user is provided, it is not necessary for a developer to develop a Web application generating the Web information for each terminal type.

For example, the Web information is information to provide on a Web browser through the Internet.

Moreover, when the communicating part receives the first request from the network, the communicating part additionally may provide a default value of the terminal type and reference Web information identification for identifying

/

the reference Web information generating part to the path
for the Web information indicated in the first request, and
the reference Web information generating part may be executed
by the reference Web information identification additionally
5 provided by the communicating part and may replace the
default value with the specified terminal type.

In the information processing apparatus, when
the first request is received, the communicating part (for
example, HTTP daemon) additionally provides the default
10 value and the reference Web information identification
beforehand. Therefore, the reference Web information
generating part is always executed with respect to the first
request.

Furthermore, the communicating part may create
15 the reference path by adding the default value before the
Web information identification for identifying the Web
information in the path for the Web information indicated
in the first request.

In the information processing apparatus, since
20 the terminal type information is set before the Web
information identification, the path after the Web
information identification can be used as a relative path.
Therefore, even if the page transition is conducted from the
reference information, the terminal type information can be
25 always succeeded to next Web information.

Moreover, the information processing apparatus may further include a Web information generating part generating the Web information; and a display information generating part generating a Web page by describing the Web information corresponding to the terminal in a display format for displaying the Web information at the terminal based on the terminal type information obtained from the reference path indicated by the second request. In addition, the display information generating part may include an XML describing part describing the Web information generated by the Web information generating part and the terminal type information in an extensible markup language; and an HTML converting part generating the Web page by converting the Web information described in the extensible markup language into a hypertext markup language in accordance with a style sheet corresponding to the Web information based on the terminal type information.

In the information processing apparatus, the display information generating part generates the Web page corresponding to the terminal type, and a generation of the Web page is conducted independent of a generation of the Web information. Therefore, it is possible to easily develop and add the Web application.

Furthermore, the information processing apparatus may include a plurality of other Web information

generating parts generating other Web information other than the Web information, the other Web information linked from the Web information by a relative path, wherein when one of the other Web information generating part corresponding to
5 the other web information generates the other Web information in response to a third request for requesting the other Web information selected by a user at the terminal displaying the Web information, the display information generating part generates the Web page for displaying the other Web
10 information suitable for the terminal at the terminal, based on the terminal type information set in the reference path.

In the information processing apparatus, even if another Web page providing another Web information is linked from the Web page providing the Web information currently
15 displayed at the terminal, it is possible to obtain the terminal type information set in the reference path in common. Therefore, the Web page can be generated by corresponding to the display screen of the terminal.

Moreover, the information processing apparatus
20 may further include a Web frame information generating part setting relative paths for the Web information and the other Web information to display for each of a plurality of frames, and generating Web frame information defining the plurality of frames to divide the Web page, wherein the reference Web
25 information generating part generates the reference web

information that includes the reference path to access the Web frame information created by adding terminal type information to a path for the Web frame information and that allows the terminal to automatically access to the reference path, and when the communicating part sends the reference Web information to the terminal as the response to the first request and receives the second request requesting the Web frame information by the reference path from the terminal, the Web frame information generating part is executed.

10 In the information processing apparatus, in a case in that the Web screen divided into a plurality of Web pages by frames, the Web frame information setting the reference path is automatically requested from the terminal. Each of the Web information and other Web information can be accessed by the relative paths, respectively, and the terminal type information can be succeeded.

 Furthermore, display information generating part may disable the Web frame information generating part based on the terminal type information obtained from the reference path indicated in the second request, and generates the Web page that allows the terminal to directly access the Web information by a relative path for the Web information requested by the first request.

 In the information processing apparatus, when the terminal is a terminal other than a PC, the frame

information is not sent to the terminal. Instead, the Web page directly accessing the Web information is generated and sent to the terminal.

Moreover, the information processing apparatus
5 may further include an image forming part forming an image;
and an image formation controlling part controlling the image
forming parts, wherein at least one of the Web information
generating part and the other Web information generating
parts obtains information concerning the image forming part
10 from the image formation controlling part and generates the
Web information based on the obtained information.

In the information processing apparatus, while
succeeding to the terminal type information, it is possible
to provide as the Web information a status of a device such
15 as a plotter or a scanner, which is mounted to the information
processing apparatus and forms an image.

Furthermore, the display information generating
part may generate the Web page by additionally providing an
image to the Web information or the other Web information
20 generated by the Web information generating part or the other
Web information generating parts, based on the terminal type
information set based on the reference path in common.

In the information processing apparatus, for
example, when the display screen of the terminal is smaller
25 than that of a regular PC, the Web page is generated so as

to display the Web information without an image.

Moreover, the display information generating part generates the Web page displaying the Web information or the other Web information generated by the Web information generating part or the other Web information generating parts, 5 in a font size suitable for the terminal, based on the terminal type information set based on the reference path in common.

In the information processing apparatus, for example, when the display screen of the terminal is smaller 10 than that of the regular PC, the Web page is generated so as to display the Web information in smaller fonts. When the display screen of the terminal is larger than that of the regular PC, the Web page is generated so as to display the Web information in bigger fonts.

Furthermore, the display information generating part may generate the Web page displaying the Web information or the other Web information generated by the Web information generating part or the other Web information generating parts, 15 by a number of letters suitable for the terminal, based on the terminal type information set based on the reference path 20 in common.

In the information processing apparatus, for example, when the display screen of the terminal is smaller than that of the regular PC, the Web page is generated so 25 as to display the Web information by fewer letters. When the

display screen of the terminal is larger than that of the regular PC, the Web page is generated so as to display the Web information by more letters in detail.

The above objects of the present invention are
5 achieved by an information processing apparatus for providing the Web page displaying the Web information by corresponding to a language used at the terminal.

The above objects of the present invention are achieved by an information processing apparatus for
10 providing the Web page displaying the Web information by corresponding to a profile of the user using at the terminal.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following, embodiments of the present
15 invention will be described with reference to the accompanying drawings.

FIG.1 is a block diagram showing a hardware configuration of an information processing apparatus according to a first embodiment of the present invention;

20 FIG.2 is a block diagram showing a functional configuration of the information processing apparatus according to the first embodiment of the present invention;

FIG.3 is a diagram showing a URL configuration according to the first embodiment of the present invention;

25 FIG.4 is a block diagram for explaining an

execution of Web applications according to the first embodiment of the present invention;

FIG.5A is a diagram showing a hash list and FIG.5B is a diagram showing another hash list according to the first embodiment of the present invention;

FIG.6 is a diagram showing a process flow for default.cgi according to the first embodiment of the present invention;

FIG.7 is a diagram showing the process flow for default.cgi according to the first embodiment of the present invention;

FIG.8 is a flowchart diagram for explaining an analyzing process for terminal information according to the first embodiment of the present invention;

FIG.9 is a diagram showing a data structure of HTTP connection information according to the first embodiment of the present invention;

FIG.10 is a diagram showing a data structure of HTTP request information according to the first embodiment of the present invention;

FIG.11 is a diagram showing a header information list according to the first embodiment of the present invention;

FIG.12 is a diagram showing a Web browser type - terminal type correspondence table according to the first

embodiment of the present invention;

FIG.13 is a diagram showing a Web browser OS - terminal type correspondence table according to the first embodiment of the present invention;

5 FIG.14 is a diagram showing an example of a default HTML output according to the first embodiment of the present invention;

FIG.15 is a diagram showing a process flow by mainFrame.cgi according to the first embodiment of the
10 present invention;

FIG.16 is a diagram showing the process flow by mainFrame.cgi according to the first embodiment of the present invention;

FIG.17 is a diagram showing an example of a
15 mainframe HTML output for a PC according to the first embodiment of the present invention;

FIG.18 is a diagram showing a process flow by topPage.cgi according to the first embodiment of the present invention;

20 FIG.19 is a diagram showing the process flow by topPage.cgi according to the first embodiment of the present invention;

FIG.20 is a diagram showing an example of a process result described in XML by topPage.cgi according to
25 the first embodiment of the present invention;

FIG.21 is a diagram showing a description example of XSL for converting the process result from XML to HTML according to the first embodiment of the present invention;

FIG.22 is a diagram showing a description example of HTML for the PC in that the process result of topPage.cgi is shown, according to the first embodiment of the present invention;

FIG.23 is a diagram showing a display example of a system status at the client PC according to the first embodiment of the present invention;

FIG.24 is a diagram showing a description example of HTML for a PDA terminal where the process result of topPage.cgi is shown, according to the first embodiment of the present invention;

FIG.25 is a diagram showing a display example of the system status at a PDA terminal according to the first embodiment of the present invention;

FIG.26 is a diagram showing a display example of "Network Settings" at the PDA terminal according to the first embodiment of the present invention;

FIG.27 is a diagram showing an unsuitable display example of "Network Settings" at the PDA terminal according to the first embodiment of the present invention;

FIG.28 is a block diagram showing a functional configuration of the information processing apparatus

according to a second embodiment of the present invention;

FIG.29 is a block diagram for explaining an execution of the Web applications according to the second embodiment of the present invention;

5 FIG.30A and FIG.30B are diagrams showing hash lists according to the second embodiment of the present invention;

FIG.31 is a diagram showing the process flow for default.cgi according to the second embodiment of the present
10 invention:

FIG.32 is a diagram showing the process flow for default.cgi according to the second embodiment of the present invention:

FIG.33 is a flowchart diagram for explaining the
15 analyzing process for the language information according to the second embodiment of the present invention;

FIG.34 is a diagram showing a header information list according to the second embodiment of the present invention;

20 FIG.35A is a diagram showing an accept language information, FIG.35B is a diagram showing available language list, and Fig.35C is a diagram showing an operation panel language stored in a predetermined storage area;

FIG.36 is a diagram showing an example of the
25 default HTML output according to the second embodiment of

the present invention;

FIG.37 is a diagram showing a process flow by netsetting.cgi according to the second embodiment of the present invention;

5 FIG.38 is a diagram showing a process flow by netsetting.cgi according to the second embodiment of the present invention;

FIG.39 is a diagram showing an example of the process result described in XML by netsetting.cgi according
10 to the second embodiment of the present invention;

FIG.40 is a diagram showing an example of the language resource according to the second invention of the present invention;

FIG.41 is a diagram showing a description example
15 of the style sheet for converting the process result from XML to HTML according to the second embodiment of the present invention;

FIG.42 is a diagram showing a description example
of the style sheet for converting the process result from
20 XML to HTML according to the second embodiment of the present invention;

FIG.43 is a diagram showing a description example
of the style sheet for converting the process result from
XML to HTML according to the second embodiment of the present
25 invention;

FIG.44 is a diagram showing an example of the network setting HTML in English showing the process result of netsetting.cgi, according to the second embodiment of the present invention;

5 FIG.45 is a diagram showing the network setting page displayed in English according to the second embodiment of the present invention;

FIG.46 is a diagram showing another Web page linked from the network setting page in FIG.45 according to
10 the second embodiment of the present invention;

FIG.47 is a diagram showing an example of the system status HTML in Japanese showing the process result of sysstatus.cgi, according to the second embodiment of the present invention;

15 FIG.48 is a diagram showing an example of a system status page in Japanese according to the second embodiment of the present invention;

FIG.49 is a block diagram showing a functional configuration of the information processing apparatus
20 according to the third embodiment of the present invention;

FIG.50 is a block diagram for explaining an execution of the Web applications according to the third embodiment of the present invention;

FIG.51 is a diagram showing a process flow by
25 rolechange.cgi according to the third embodiment of the

present invention;

FIG.52 is a diagram showing the process flow by netsetting.cgi according to the third embodiment of the present invention;

5 FIG.53 is a diagram showing the process flow by netsetting.cgi according to the third embodiment of the present invention;

FIG.54 is a diagram showing a correspondence between the profile information to set in the URL and the profile of the user according to the third embodiment of the present invention;

10

FIG.55 is a diagram showing an example of the HTML response calling the network setting page for the system administrator according to the third embodiment of the present invention;

15

FIG.56 is a diagram showing an example of the process result described in XML by netsetting.cgi according to the third embodiment of the present invention;

FIG.57 is a diagram showing a description example of the style sheet for converting the process result from XML to HTML according to the third embodiment of the present invention;

20

FIG.58 is a diagram showing a description example of HTML for the system administrator in that the process result of the netsetting.cgi is shown, according to the third

25

embodiment of the present invention; and

FIG.59 is a diagram showing the network setting page for the system administrator according to the third embodiment of the present invention.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following, embodiments of the present invention according to an information processing apparatus will be described with reference to the accompanying
10 drawings.

[First Embodiment]

An information processing apparatus according to a first embodiment of the present invention includes at least one of a plurality of different image forming functions such
15 as a printer, a FAX, and a copier, and also provides information concerning the image forming functions by a plurality of Web applications. In the present invention, for the sake of convenience, a case in that information concerning a copying process and a plotter for conducting
20 a copy will be mainly described. The information processing apparatus provides the information by a suitable size for a display screen of a terminal requesting the information.

FIG.1 is a block diagram showing a hardware configuration of the information processing apparatus
25 according to the first embodiment of the present invention.

In FIG.1, the information processing apparatus 100 is controlled by a computer, and includes a CPU (Central Processing Unit) 11, a ROM (Read-Only Memory) 12, a RAM (Random Access Memory) 13, a non-volatile RAM 14, a real time clock 15, an EthernetTM I/F (Interface) 21, a USB (Universal Serial Bus) 22, an IEEE 1284 (Institute of Electrical and Electronics Engineers 1284) 23, a hard disk I/F 24, an engine I/F 25, and an RS-232C I/F 26, which are mutually connected through a system bus B.

10 The CPU 11 controls the information processing apparatus 100 according to the programs stored in the ROM 12. For example, the RAM 13 includes an area to assign to each resource connected to one of the interfaces 21 through 26. The non-volatile RAM 14 stores information necessary for
15 a process by the CPU 11 to control the information processing apparatus 100. The real time clock 15 clocks a present time, and also is used by the CPU 11 to synchronize the process.

 The EthernetTM I/F 21 is used to connect to an interface cable for the EthernetTM I/F 21 such a 10 BASE-T
20 or 100 BASE-TX. The USB I/F 22 is used to connect to an interface cable based on the USB standard. The IEEE1284 23 is used to connect to an interface cable based on the IEEE1284 standard.

 The hard disk I/F 24 is used to connect to a hard
25 disk 34. Document data concerning a document that is sent

through a network to print or image data after a printing process is stored in the hard disk 34 through the hard disk I/F 24. The engine I/F 25 is used to connect to a plotter 35-1 for printing to a predetermined medium based on the document data and a scanner 35-2 for reading the image data. The RS-232C I/F 26 is used to connect to an operation panel 36 that displays information to a user or obtains information input or set by the user.

Next, a functional configuration of the information processing apparatus 100, which includes the hardware configuration as shown in FIG.1, conducts a plurality of different image forming processes, and includes a plurality of Web applications, will be described with reference to FIG.1.

FIG.2 is a block diagram showing the functional configuration of the information processing apparatus according to the first embodiment of the present invention. In FIG.2, the information processing apparatus 100 is capable of connecting to terminals 40 including a client PC 41, a mobile phone 42, and a PDA (Personal Digital Assistant) terminal 43, which have different utilization forms of a display screen. The information processing apparatus 100 is a computer to provide information as a response with respect to a request sent from each of the terminals 40.

The information processing apparatus 100 mainly

includes a network controlling part 101, a sequence control library 110, a Web application distribution common library 120, a Web page handler 200, a SOAP (Simple Object Access Protocol) library 201, an XML (eXtensible Markup Language) library 203, an XSLT (XSL Transformations) processor 205, a Web page function (WPF) 300, a printer controlling part 103, and a scanner controlling part 105.

The network controlling part 101 includes at least an HTTP daemon 2 for conducting a communication control in accordance with an HTTP (Hyper Text Transfer Protocol). The network controlling part 101 receives the request from each terminal 40 and provides information as a response with respect to the request.

In order to execute a predetermined process so as to succeed to attribute information showing attributes concerning a utilization form of a Web browser of the terminal 40 while a user conducts page transitions (browse one Web page linked from another Web page) among a plurality of Web applications 301, when the HTTP daemon 2 receives the request from the terminal 40, and additionally provides a temporary common path information, and a Web application ID and a CGI (Common Gateway Interface) which are referred to execute the predetermined process, to the URL indicated by the request. The HTTP daemon 2 adds necessary information and creates the URL as shown in FIG.3. FIG.3 is a diagram showing a URL

configuration according to the first embodiment of the present invention. In FIG.3, the URL is mainly formed by a common path information 60a and a relative path information 60b.

5 When the HTTP daemon 2 receives a first page request from the terminal 40, for example, only "http://AAA" is indicated as the URL. The HTTP daemon 2 additionally provides predetermined
10 "/TERMINAL/PROFILE/LANG/webDefaultApl/default.cgi" to the URL.

 For example, the URL formed as described above includes a protocol type 61 for specifying access means such as the http, an IP address 62 shown as "AAA", a terminal type information 63a shown as "TERMINAL", a profile information
15 63b shown as "PROFILE", a language information 63c shown as "LANG", a Web application ID 64 shown as "webDefaultApl", and page information 65 shown as "default.cgi".

 The protocol type 61, the IP address 62, the terminal type information 63a, the profile information 63b,
20 the language information 63c are set as the common path information 60a. After that, the common path information 60a is succeeded every time at the page transition, and is referred by the plurality of Web applications 301 being chained by the page transition. And the relative path
25 information 60b is formed by the Web application ID 64 and

the page information 65.

Referring to FIG.2 again, explanation of each processing part will be continued.

The sequence control library 110 is a processing
5 part that is shared with the plurality of Web applications
301 and handles by a predetermined sequence controlling
process a difference between a process sequence of sending
and receiving data through the Internet 16 and another
process sequence of sending and receiving data to/from each
10 of the Web applications 301.

The Web application distribution common library
120 is a processing part that is shared with the plurality
of Web applications 301, and that analyzes a request from
the terminal 40 and generates a response for the terminal
15 40. The Web application distribution common library 120
converts the response described in XML by the Web page handler
200 into the response described in a display format by HTML
(HyperText Markup Language) corresponding to the terminal
type of each terminal 40 by using the XSLT processor 205.

20 The Web page handler 200 is a processing part that
converts a process language understandable for the Web
applications 301 into another process language
understandable in the communication control conducted with
the terminal 40 for the request and the response. The Web
25 page handler 200 calls one Web application 301 corresponding

to the request via a CGI indicated by the request. Also, the Web page handler 200 sends a serialization request to the SOAP library 201 to serialize process result data provided from the Web page function 300.

5 The SOAP library 201 converts the process result data given by variables of C language into a description in XML so as to serialize the process result. In the first embodiment, serialization means to describe the process result provided from the Web page function 300 in XML.

10 The XML library 203 is used by the SOAP library 201 to serialize the process result by describing in XML. Also, the XML library 203 is used by the XSLT processor 205 to generate the process result described in HTML.

 The XSLT processor 205 converts the process
15 result described in XML into HTML by using the XML library 203 based on a style sheet 430 described in XSL (eXtensible Stylesheet Language) corresponding to the Web application 301 indicated by the request from the terminal 40. The style sheet 430 is prepared beforehand by corresponding to each
20 Web application 301 and instructs a conversion method for each size of the display screens.

 When the Web page function 300 is called from the Web page handler 200, for example, inquires the printer controlling part 103 or the scanner controlling part 105
25 mounted to the information processing apparatus 100 through

an API (Application Program Interface) 17, obtains information showing a status of the plotter 35-1 or the scanner 35-2, and then provides the information to the Web page handler 200. Moreover, the Web page function 300
5 inquires the network controlling part 101 through the API 17, obtains information from the network controlling part 101, and provides the information to the Web page handler 200.

Next, a detailed configuration for executing the
10 Web applications will be described with reference to FIG.4, FIG.5A and FIG.5B. FIG.4 is a block diagram for explaining an execution of the Web applications according to the first embodiment of the present invention. FIG.5A and FIG.5B are diagrams showing hash lists according to the first embodiment
15 of the present invention. In FIG.4, for example, in order to provide information based on the configuration of the URL as shown in FIG.3, the Web page handler 200 includes a default handler 210 executed at a first request from the terminal 40, a network setting handler 220 executed by a page
20 transition in accordance with the instruction from the terminal 40, a system configuration information providing handler 230 similarly executed by page transition, and a like.

Corresponding to the handlers in the Web page
25 handler 200, respectively, the Web page function 300 includes

the plurality of Web applications 301: a Web default application 310, a Web network setting application 320, a Web system configuration information providing application 330, and a like.

5 Until an initial display screen is displayed at the terminal 40, the default handler 210 sequentially calls the Web default application 310 through "default.cgi", "mainFrame.cgi", "manuPage.cgi", "topPage.cgi", and "headerPage.cgi" indicated by the page information 65 in
10 accordance with a format of the URL shown in FIG.3. As a result, for example, a status of the device such the plotter 35-1 or scanner 35-2 mounted in the information processing apparatus 100 is displayed at the terminal 40.

 The network setting handler 220 calls a function
15 for the Web network setting application 320 for setting up network setup information inputted by a user of the terminal 40 in the information processing apparatus 100. In addition, the system configuration information providing handler 230 calls the Web system configuration information providing
20 application 330 so as to obtain a system configuration information of the information processing apparatus 100 in response to a request from the terminal 40.

 The Web application distribution common library
120 obtains the Web application ID 64 from a URL, and refers
25 to a hash list 50a shown in FIG.5A. When the Web application

ID 64 shows "webDefaultApl", the Web application distribution common library 120 executes "default_handler". In the same manner, when the Web application ID 64 shows another Web application ID, the Web application distribution
5 common library 120 refers to the hash list 50a, and executes a handler corresponding to the Web application ID to be executed.

In addition, each of the handlers 210, 220, and 230 in the Web page handler 200 obtains the page information
10 65 from the URL, refers to the hash list shown in FIG.5B, and calls a function corresponding to the page information 65. For example, when the page information 65 shows "default.cgi", "default()" is obtained to call as a function. Similarly, when the page information 65 shows another CGI,
15 each of the handlers 210, 220, and 230 refers to hash list 50b and obtains a function to call.

Moreover, in order to conduct the XSL conversion request which converts the process result described by XML to the XSLT processor 205 into HTML, the Web application
20 distribution common library 120 obtains the page information 65 from the URL specified as a Web page function ID, and obtains a corresponding style sheet 430 by referring to the hash list 50b shown in FIG.5B. For example, when the page information 65 shows "topPage.cgi", the Web application
25 distribution common library 120 obtains "topPage.xsl" as a

style sheet necessary for the XSL conversion from the hash list 50b. Similarly, when the page information 65 is another CGI, the Web application distribution common library 120 obtains a style sheet necessary for the XSL conversion by referring to the hash list 50b.

In FIG.4, FIG.5A, and FIG.5B, when the page information 65, as the Web page function ID, of the URL is "default.cgi", the function default() is executed, and the terminal type of the terminal 40 is determined. Accordingly, the terminal type information of the URL which is temporarily created by the HTTP daemon 2 is replaced with the determined terminal type and the initial display screen where the URL showing the determined terminal type is set is created.

When the page information 65 is "mainFrame.cgi", a function mainFrame() is executed, and a predetermined CGI is set for each of frames forming the initial display screen. For example, the function mainFrame() generates information so as to configure a frame displaying a menu page, a frame displaying a top page, and a frame displaying a header page.

When the page information 65 is "menuPage.cgi", the function menuPage() is executed, and the information for creating a menu page is generated. When the page information 65 is "topPage.cgi", a function "topPage.cgi" is executed. For example, the information is generated so as to create a top page displaying a status of a printer as a status of

the plotter 35-1. When the page information 65 is "headerPage.cgi", a function headerPage() is executed so as to generate information for creating the top page.

Moreover, when the page information 65 is
5 "netsetting.cgi", a function netsetting() is executed so as to generate the information for creating a page for the system setting. When the page information 65 is "sysconfig.cgi", a function sysconfig() is executed, information showing a system configuration is generated.

10 For the sake of convenience, names of the Web application ID and the Web page handler are unified. But it is not limited to do so since the hash list 50a corresponds the Web application ID to the Web page handler. Also, names of the Web page function ID, the function, the style sheet
15 are unified in the same manner. But it is not limited to do so since the hash list 50b corresponds the Web page function ID, the function, and the style sheet each other.

Next, a process flow until information is provided with respect to the first request from the terminal
20 40 will be described. FIG.6 and FIG.7 are diagrams showing the process flow for default.cgi according to the first embodiment of the present invention.

In FIG.6, the terminal 40 sends a request additionally providing user agent information by using a GET
25 method of the HTTP (step S11). For example, the terminal 40

sends the request by indicating a URL "http://AAA".

When the information processing apparatus 100 receives this request, the HTTP daemon 2 of the information processing apparatus 100 additionally provides the terminal
5 type information 63a, the profile information 63b, the language information 63c, the Web application ID 64, the page information 65 to the URL "http://AAA", and then sends this request to the sequence control library 110 (step S12). For example, the HTTP daemon 2 additionally provides "TERMINAL"
10 as the terminal type information 63a, "PROFILE" as the profile information 63b, "LANG" as the language information 63c, "webDefaultApl" as the Web application ID 64, and "default.cgi" as the page information 65, to the URL "http://AAA", so as to form
15 "http://AAA/TERMINAL/PROFILE/LANG/webDefaultApl/default.cgi".

The sequence control library 110 calls the Web application distribution common library 120 (step S13). When calling the Web application distribution common library
20 120, the sequence control library 110 sets the HTTP connection information showing information concerning a connection with the terminal 40, and the hash lists 50a and 50b as arguments. In the following, the hash lists 50a and 50b are generically called hash lists. That is, the hash
25 lists include the hash lists 50a and 50b and other hash lists.

The HTTP connection information uniquely specifies the connection with the terminal 40 until the connection is disconnected.

The Web application distribution common library
5 120 specifies and calls the default handler 210
("default_handler") from the hash list 50a, as the Web page
handler 200 corresponding to the Web application ID 64
showing "webDefaultApl" based on the URL generated by the
HTTP daemon 2 (step S14).

10 In the Web page handler 200, the default handler
210 obtains the page information 65 showing "default.cgi"
from the URL, and specifies and calls the function default()
from the hash list 50b as the Web page function 300
corresponding to "default.cgi" (step S15). In this case, the
15 HTTP connection information is set as the argument. For
example, in a case in that the Web page function 300 is
developed by C language, the Web page handler 200 converts
into a process type of C language and then calls the function
default().

20 By executing the function default(), based on the
HTTP connection information, terminal information is
analyzed and a URL calling the initial display screen is
created by including the common path information 60a
determined by the function default () (step S16). A process
25 result data including the URL is returned to the default

handler 210 in the Web page handler 200 (step S17). In a process by default.cgi, the common path information 60a is determined, and a URL is determined by the common path information 60a and the relative path information 60b for determining a frame configuration of the initial display screen. For example, "/pc/admin/ja" is determined as the common path information 60a and
5 "/webDefaultApl/mainFrame.cgi" for dividing the initial display screen into a plurality of display areas by frames is determined as the relative path information 60b.
10

The default handler 210 sends a serialization request to the SOAP library 201 in order to describe the process result data in XML (Step S18). For example, the SOAP library 201 creates a DOM (Document Object Model) based on the process result data shown by a C language structure,
15 additionally provides necessary elements and attributes (step S19), and describes the process result data in XML by the XML library 203 (step S20). The process result data described in XML is provided to the default handler 210 as
20 the serialization result by the SOAP library 201 (step S21). In the Web page handler 200, the default handler 210 provides the serialization result as display data "Response DOM" to display at the terminal 40, to the Web application distribution common library 120 (step S22).

25 In order to convert the display data described

in XML into a description of HTML corresponding to the terminal type of the terminal 40, the Web application distribution common library 120 refers to the hash list 50b, obtains the style sheet "default.xsl" corresponding to the page information 65 showing "default.cgi", and sends the XSL conversion request to the XSLT processor 205 (step S23). The display data "Response DOM" and the style sheet "default.xsl" are set as arguments for the XSL conversion request.

When the XSLT processor 205 receives the XSL conversion request, the XSLT processor 205 executes the style sheet "default.xsl" indicated by the argument. Accordingly, the XSLT processor 205 analyzes syntax of the display data "Response DOM" described in XML (parse XML, creates a DOM, additionally provides elements and attributes (step S24), and converts into the description of HTML by using the XML library 203 (step S25). The XSLT processor 205 provides the description of HTML to the Web application distribution common library 120 as a XSL conversion result (step S26).

The process result described in HTML by the Web page function 300 when the page information 65 shows "default.cgi" is output as a default HTML to the Web application distribution common library 120. In the default HTML, "mainFrame.cgi" is described in HTML to be called. The default HTML is output as a default HTML response.

The default HTML response is sequentially

provided from the Web application distribution common library 120 to the sequence control library 110 (step S27), and is provided from the sequence control library 110 to the HTTP daemon 2 (step S28). After that, the default HTML
5 response is sent as a response with respect to the request of the terminal 40 in step S11 by the HTTP daemon 2 (step S29). Then, the process flow for executing the Web default application 310 by the default.cgi is terminated.

In step S17, the common path information 60a is
10 determined and simply the common path information 60a is added to the relative path information 60b. Accordingly, the Web default application 310 may describe the process result in HTML and output the process result described in HTML. Thus, steps S18 through S26 may be omitted.

15 Next, an analyzing process for the terminal information executed by the function default () in step S16 shown in FIG.6 will be described with reference to FIG.8 through FIG.11 in detail. FIG.8 is a flowchart diagram for explaining the analyzing process for the terminal
20 information according to the first embodiment of the present invention. FIG.9 is a diagram showing a data structure of the HTTP connection information according to the first embodiment of the present invention. FIG.10 is a diagram showing a data structure of the HTTP request information
25 according to the first embodiment of the present invention.

FIG.11 is a diagram showing a header information list according to the first embodiment of the present invention. The data structures shown in FIG.9 through FIG.11 are referred by the analyzing process for the terminal
 5 information shown in FIG.8.

Prior to explanation of the analyzing process in FIG.8, each of the data structures shown in FIG.9 through FIG.11 will be described. In FIG.9, the HTTP connection information 340 is information generated for each connection.
 10 In the HTTP connection information 340, a script 346 describing "HTTP_REQUEST_INFO *request" indicates a pointer to a content of the request from the terminal 40 and a script 347 describing "HTTP_RESPONSE_INFO *response" indicates a pointer to a content of the response for the terminal 40.
 15 The HTTP request information is stored in a area indicated by the pointer shown by the script 346, as shown in FIG.10.

In FIG.9, reference numerals 1340, 1346, and 1347 will be referred in a second embodiment of the present invention.

20 In FIG.10, the HTTP request information 350 includes a remote address 351 showing an address of the terminal 40 which sent the request, a local address 352 showing an host address at a side where the request is received, a request method 353 such as POST, GET, or a like, a request
 25 URL 354 showing an URL of the request, an HTTP version 355

of the request, a header information list 360, and a encoded information list 357.

In the request URL 354, the URL formed by the common path information 60a and the relative path information 60b as shown in FIG.3 is set by the sequence control library 110. The HTTP request information 350 is provided to the Web page handler 200 and to the Web page function 300 at the same time of the HTTP connection information 340. Accordingly, the Web page handler 200 and the Web applications 301 share and refer to the common path information 60a.

In FIG.10, reference numerals 1350, 1351, 1352, 1353, 1354, 1355, 1360, and 1357 will be referred in the second embodiment of the present invention.

And for example, the header information list 360 is structured as shown in FIG.11. As shown in FIG.11, the header information list 360 includes user agent information 365 showing "User-Agent:Mozilla/4.0{compatible;MSIE 6.0;Windows NT 5.0;Q312461;NET CLR 1.0.3705)". The user agent information 365 includes the terminal type of the terminal 40. Thus, this script of the user agent information 365 is analyzed, so as to provide information corresponding to the size of the display screen of the terminal 40.

In FIG.8, in response to a call of the function(), the Web default application 310 obtains the HTTP request information 350 from the HTTP connection information 340

(step S1). Moreover, the Web default application 310 obtains the user agent information 365 from the HTTP request information 350 (step S2). Then, based on a Web browser type of the user agent information 365, the Web default
5 application 310 refers to a Web browser type - terminal type correspondence table (FIG.12) and specifies the terminal type of the terminal 40 (step S3).

The Web default application 310 determines whether or not the terminal type is determined based on the
10 Web browser type (step S4). When the terminal type is determined, the Web default application 310 goes to step S38. When the terminal type is not determined, the Web default application 310 refers to a Web browser OS - terminal type correspondence table based on the Web browser OS of the user
15 agent information 365 and specifies the terminal type of the terminal 40 (step S5).

The Web default application 310 determines whether or not the terminal type is determined based on the Web browser OS (step S6). When the terminal type is not
20 determined, the default application 310 outputs error information showing that the terminal type is not supported (step S7), and then the analyzing process for the terminal information is terminated. In step S7, the Web default application 310 sets a predetermined device type as the
25 terminal type of the terminal 40, instead of outputting the

error information showing that the terminal type is not supported, and then the Web default application 310 goes to step S8.

On the other hand, in steps S4 and S6, when the
 5 terminal type is determined, the Web default application 310 sets the terminal type to the terminal type information 63a of the URL (step S8), and then terminates the analyzing process for the terminal information.

FIG.12 is a diagram showing the Web browser type
 10 - terminal type correspondence table according to the first embodiment of the present invention. In FIG.12, the Web browser type - terminal type correspondence table 370 includes items of the Web browser type, the terminal type, and the like. The terminal type corresponding the Web
 15 browser type is managed in the Web browser type - terminal type correspondence table 370.

For example, as the Web browser type, "DOCOMOTM", "xiinoTM", "MSPIETM", "HandHTTPTM", "MSIETM", "MozillaTM", "mozilla/5TM", and "Netscape6TM" are managed in the Web
 20 browser type - terminal type correspondence table 370.

The terminal types are "IMODETM", "PDA", "0", "PC", and a like. The terminal type corresponding to the Web browser type "DOCOMOTM" is "IMODETM". The terminal type corresponding to the Web browser type "xiinoTM", and "MSPIETM",
 25 "HandHTTPTM" is "PDA". The terminal type corresponding to

the Web browser type "Mozilla™", "mozilla/5™", and "Netscape6™" is "PC". The terminal types are not limited to the above-described terminal types but various terminal types can be managed.

5 The terminal type "0" denotes that the terminal type cannot be specified. In a determination process in step S4 of FIG.8, the terminal type is not determined. For example, in a case of a request from InternetExploer™, generally, the Web browser type "MSPIE™" is set to the user agent information
10 365 when the terminal type is "PDA", and the Web browser type "MSIE™" is set to the user agent information 365 when the terminal type is "PC". However, even if the terminal type is "PDA", there is a case in that the Web browser "MSIE™" is set to the user agent information 365. Accordingly, since
15 the terminal type corresponding to the Web browser type "MSIE™" cannot be specified beforehand, "0" is set to the terminal type for the Web browser type "MSIE™".

In a case in that the terminal type cannot be specified as described above, a correspondence table shown
20 in FIG.13 is referred to. FIG.13 is a diagram showing the Web browser OS - terminal type correspondence table according to the first embodiment of the present invention. In FIG.13, the Web browser OS - terminal type correspondence table 380 includes items of the Web browser OS, the terminal type, and
25 the like. The Web browser OS corresponding to the terminal

type is managed.

For example, as the Web browser OS, there are
 "Windows 3.1TM", "Windows 95TM", "Windows 98TM", "Windows METM",
 "Windows NTTM", "Windows 2000TM", "Windows XPTM", "Mac 68KTM",
 5 "Mac Power PCTM", "SolarisTM", "LinuxTM", "Free BSDTM", "AIXTM",
 "IRIXTM", "HPTM", "OS/2TM", "Windows CETM", and a like.

There are "PDA", "PC", and a like as the terminal
 types. The mobile phone 42 is included in the terminal type
 "PDA". In the Web browser OS - terminal type correspondence
 10 table 380 shown in FIG.13, the terminal type corresponding
 to the Web browser OS from "Windows 3.1TM" to "OS/2TM" is "PC".
 And the terminal type corresponding to the Web browser OS
 "Windows CETM" is "PDA".

The terminal type can be specified by referring
 15 to the Web browser type - terminal type correspondence table
 370 and the Web browser OS - terminal type correspondence
 table 380.

The default HTML output by default.cgi will be
 described with reference to FIG.14. FIG.14 is a diagram
 20 showing an example of the default HTML output according to
 the first embodiment of the present invention. In FIG.14,
 the default HTML 400 is not displayed at the terminal 40,
 but a script 401 that is JavascriptTM calls the top page.

By a script 402 showing
 25 "self.document.cookie="cookieOnOffchecker=on; path="/",

information concerning the Web browser of the terminal 40 is obtained. By a scrip 403 showing
`"self.location.pathname="/pc/admin/ja/webDefaultApl/mainframe.cgi"`, the terminal type "pc" is succeeded, and the
 5 Web default application 310 of the Web page function 300 is executed. That is, a mainframe HTML is requested by
`"mainframe.cgi"`. During a series of page transitions conducted by a user after that, an absolute path is indicated by a script 403 to be a reference for a relative path indicated
 10 by `<a href>` tag.

In a case in which information is provided to the client pc 41 through the Internet 16, the display screed is often divided into a plurality of display areas by frames. The default output is illustrated in such a case in FIG.14.
 15 On the other hand, in a case in that the initial display screen is displayed without dividing into the plurality of display areas, for example, the script 403 describes
`"self.location.pathname="/pc/admin/ja/webDefaultApl/topPage.cgi"`. The top page is directly called to provide and
 20 display information.

In the following, a process will be described in that information is provided corresponding to the terminal type of the terminal 40 in a case of dividing the display screen into the plurality of display areas by frames.

25 After that, when the page transition is conducted,

only the relative path information 60b is indicated but the terminal type "PC" included in the common path information 60a is always succeeded. That is, the same common path information 60a is shared and referred by the plurality of the Web applications 301.

FIG.15 and FIG.16 are diagrams showing a process flow by mainFrame.cgi according to the first embodiment of the present invention. In FIG. 15, the terminal 40 requests a mainframe HTML (mainfram HTML request) (step S31).

10 "/pc/admin/ja/webDefaultApl/mainFrame.cgi" is indicated, and the mainfram HTML request is conducted by a GET method attaching with form data. The HTTP daemon 2 of the information apparatus 100 sends the HTTP connection information 340 and the hash lists to the sequence control library 110 (step S32).

In this case, by the HTTP daemon 2, "GET" is set to the request method of the HTTP request information 350 related to the HTTP connection information 340, and "/pc/admin/ja/webDefaultApl/mainFrame.cgi" is set to the request URL 354. By this indication, when a next request is received from the terminal 40 by the relative path after that, the common path information 60a showing "/pc/admin/ja" can be referred. Accordingly, it is easily determined that the terminal type of the terminal 40 is "PC." Also, the form data received from the terminal 40 is set to the hash lists by

the HTTP daemon 2.

The sequence control library 110 calls the Web application distribution common library 120 (step S33). In this case, the sequence control library 110 sets the HTTP
5 connection information showing information concerning the connection with the terminal 40 and the hash lists as arguments.

The Web application distribution common library 120 specifies and calls the default handler 210
10 ("default_handler") from the hash list 50a as the Web page handler 200 corresponding to the Web application ID 64 indicating "webDefaultApl" based on the URL (step S34).

In the Web page handler 200, the default handler 210 obtains the page information indicating "mainFrame.cgi"
15 from the URL, and specifies and calls the function mainFrame() from the hash list 50b as the Web page function 300 corresponding to "mainFrame.cgi" (step S35). In this case, the HTTP connection information is set as an argument. For example, in a case in that the Web page function 300 is
20 developed by C language, the Web page handler 200 converts into a process type of C language and calls the function mainFrame().

By executing the function mainFrame(), frame information to form the initial display screen (topPage.cgi)
25 is created (step S36). The frame information is sent to the

default handler 210 in the Web page handler 200 as the process result data (step S37).

In the following, the serialization process for describing in XML in steps S38, S39, S40, S41, and S42 is
5 the same as the serialization process in steps S18, S19, S20, S21, and S22 and explanation thereof will be omitted.

In order to convert the display data described in XML into a description in HTML corresponding the terminal type of the terminal 40, the Web application distribution
10 common library 120 refers to the hash list 50b, obtains the style sheet "mainFrame.xsl" corresponding to the page information 56 indicating "mainFrame.cgi", and conducts the XSL conversion request with respect to the XSLT processor 205 (step S43). In this case, the display data "Response DOM"
15 and the style sheet "mainFrame.xsl" are set as the arguments.

When the XSLT processor 205 receives the XSL conversion request, the XSLT processor 205 executes the style sheet "mainFrame.xsl" indicated by the argument. Accordingly, the XSLT processor 205 selects one template
20 corresponding to the terminal type from descriptions of the style sheet, analyzes a syntax of the display data "Response DOM" described in XML (parse XML), creates a DOM, additionally provides elements and attributes (step S44), and converts into the description of HTML by using the XML
25 library 203 (step S45). When the terminal type information

63a shows "PC", HTML data for dividing the display screen into the plurality of display areas by frames is output. On the other hand, when the terminal type information 63a shows "PDA", HTML data described by JavaScript™ for directly
5 calling the top page is output.

The XSLT processor 205 provides the description in HTML as the XSL conversion result to the Web application distribution common library 120 (step S46). The process result described in HTML by the Web page function 300 in a
10 case in that the page information 65 shows "mainFrame.cgi" is output to the Web application distribution common library 120 as the mainframe HTML. The mainfram HTML is described in HTML so that "manuPage.cgi" is called from a frame forming the menu page, "topPage.cgi" is called from a frame forming
15 the top page, and "headerPage.cgi" is called from a frame forming the header page.

This mainframe HTML response is sequentially provided from the Web application distribution common library 120 to the sequence control library 110 (step S47),
20 and from the sequence control library 110 to the HTTP daemon 2 (step S48). Accordingly, the mainframe HTML response is sent to the terminal 40 in response to the request of the terminal 40 in step S31 in accordance with HTTP by the HTTP daemon 2 (step S49). Then, the process flow executed by the
25 mainFrame.cgi is terminated.

A mainframe HTML output by mainFrame.cgi in a case in that the terminal 40 is the client PC 41 will be described with reference to FIG.17. FIG.17 is a diagram showing an example of the mainframe HTML output for the PC according to the first embodiment of the present invention. In FIG.17, the mainframe HTML 410 creates three frames on the Web browser of the terminal 40 by a script 411, and a page from each <frame> tag is called through a CGI.

A script 412 showing <frame noresize
 10 src="/webDefaultApl/headerPage.cgi" name="header"
 marginheight="0" marginwidth="0" scrolling="no"> displays
 the header page in a frame. By a script 413 showing
 "/webDefaultApl/headerPage.cgi", the default handler 210 is
 executed based on "webDefaultApl", the function headerPage()
 15 of the Web default application 310 is executed based on
 "headerPage.cgi", and then the header page is displayed in
 the frame.

Also, a script 414 showing <frame
 src="/webDefaultApl/menuPage.cgi"
 20 name="menu"marginheight="0" marginwidth="0"
 scrolling="auto"> displays the menu page in a frame. By a
 script 415 showing "/webDefaultApl/menuPage.cgi", the
 default handler 210 is executed based on "webDefaultApl",
 the function menuPage() of the Web default application 310
 25 is executed based on "menuPage.cgi"; and the menu page is

displayed in the frame.

Furthermore, a script 416 showing <frame
src="/webDefaultApl/topPage.cgi" name="top"
marginheight="0" marginwidth="0" scrolling="auto">

5 displays the top page in a frame. By the script 417 showing
"/webDefaultApl/topPage.cgi", the default handler 210 is
executed based on "webDefaultApl", the function topPage()
of the Web default application 310 is executed based on
"topPage.cgi", and the top page is displayed in the frame.
10 Since the scripts 412, 414, and 416 indicates only relative
path information 60b, the common path information 60a is
indicated by the URL.

In FIG.17, when the terminal 40 is the mobile
phone 42 or the PDA terminal 43, the mainframe HTML may be
15 created so as to call only topPage.cgi without structuring
frames. For example, in the mainframe HTML, similar to the
description of the default HTML output shown in FIG.14,
jumpToTopPage() may be described so as to directly call
topPage.cgi by
20 "self.location.pathname="/pda/admin/ja/webDefaultApl/top
Page.cgi"", instead of describing jumpToMainFrame().

FIG.18 and FIG.19 are diagrams showing a process
flow by topPage.cgi according to the first embodiment of the
present invention. In FIG.18, the terminal 40 requests an
25 HTML for displaying a status of the plotter 35-1 or the scanner

350-2 mounted to the information processing apparatus 100 (top page HTML request) (step S51). The top page HTML request is conducted by the GET method in which "topPage.cgi" is indicated and the form data is attached.

5 The HTTP daemon 2 of the information processing apparatus 100 sends the HTTP connection information 340 and the hash lists to the sequence control library 110 (step S52). In this case, the HTTP daemon 2 sets "GET" to the request method of the HTTP request information 350 related to the
10 HTTP connection information 340, and indicates "topPage.cgi" to the URL of the request. In addition, the HTTP daemon 2 sets the form data received from the terminal 40 to the hash lists.

 The sequence control library 110 calls the Web
15 application distribution common library 120 (step S53). In this case, the sequence control library 110 sets the HTTP connection information and the hash lists as arguments.

 The Web application distribution common library 120 specifies and calls the default handler 210
20 ("default_handler") from the hash list 50a as the Web page handler 200 corresponding to the Web application ID 64 showing "webDefaultAp1" based on the URL (step S54).

 In the Web page handler 200, the default handler 210 obtains the page information 65 showing "topPage.cgi",
25 and specifies and calls the function topPage() from the hash

list 50b as the Web page function 300 corresponding to "topPage.cgi" (step S55). In this case, the HTTP connection information 340 is set as an argument.

For example, in a case in that the Web page
5 function 300 is developed by C language, the Web page handler 200 converts into a process type of C language and calls the function topPage().

By executing the function topPage(), the Web
default application 310 requests information including a
10 device name, a comment, and a like to the network controlling part 101 through the API 17, in order to display the status of a device (for example, plotter 35-1 as the printer) at the initial display screen (topPage.cgi) (step S56-2). The network controlling part 101 provides the information
15 including the device name, the comment, and the like in response to the request (step S56-4).

For example, the Web default application 310 of
the Web page function 300 requests the status of the printer
to the printer controlling part 103 through the API 17
20 (printer status request) (step S56-6). The printer
controlling part 103 provides the status of the plotter 35-1 as a printer status to the Web default application 310 (step S56-8).

Then, the Web default application 310 provides
25 the printer status, and the terminal type information 63a,

the profile information 63b and the language information 63c from the request URL 354 of the HTTP request information 350 as the process result data to the default handler 210 in the Web page handler 200 (step S57).

5 In the following, the serialization process for describing in XML in steps S58, S59, S60, S61, and S62 is the same as the serialization process in steps S18, S19, S20, S21, and S22, and explanation thereof will be omitted.

 In order to convert the display data described
10 in XML into a description of HTML corresponding to the terminal type of the terminal 40, the Web application distribution common library 120 refers to the hash list 50b, obtains the style sheet "topPage.xsl" corresponding to the page information 56 showing "topPage.cgi", and conducts the
15 XSL conversion request with respect to the XSLT processor 205 (step S63). In this case, the display data "Response DOM" and the style sheet "topPage.xsl" are set as arguments. When the XSLT processor 205 receives the XSL conversion request, the XSLT processor 205 executes the style sheet "topPage.xsl"
20 indicated in the argument. Accordingly, the XSLT processor 205 selects one template corresponding to the terminal type from descriptions of the style sheet, analyzes a syntax of the display data "Response DOM" described in XML (parse XML), creates a DOM, additionally provides elements and attributes
25 (step S64), and converts into the description of HTML by using

the XML library 203 (step S65).

XSLT processor 205 provides the description of HTML as the XSL conversion result to the Web application distribution common library 120 (step S66).

5 The process result described in HTML by the Web page function 300 in a case in that the page information 65 is "topPage.cgi" is output to the Web application distribution common library 120 as a top page HTML. Information concerning the status of the plotter 35-1 is
10 described in the top page HTML.

This top page HTML response is provided from the Web application distribution common library 120 to the sequence control library 110 (step S67), and then is provided from the sequence control library 110 to the HTTP daemon 2
15 (step S68). Subsequently, the HTTP daemon 2 sends the top page HTML response as a response in accordance with HTTP with respect to the request sent from the terminal 40 in step S51 (step S69). Then, the process flow executed by topPage.cgi is terminated.

20 When the terminal 40 is the client PC 41, processes by headerPage.cgi and manuPage.cgi called from frames are executed in the same manner described above. Accordingly, the display screen divided by frames is displayed at the Web browser of the client PC 41. On the other
25 hand, when the terminal 40 is the mobile phone 42 or the PDA

terminal 43, since the display screen is not divided by the frames, only the top page is displayed at the display screen.

The process result described in XML will be described. FIG.20 is a diagram showing an example of the process result described in XML by topPage.cgi according to
 5 the first embodiment of the present invention.

In an XML 420 shown in FIG.20, the process result by the function topPage() of the Web default application 310 is shown by a script 421 showing from <networkResponse> to
 10 </networkResponse>. A script 422 showing <terminal>pc</terminal> shows that the terminal 40 is the client PC 41, a script 423 showing <language>ja</language> shows that a language of the Web browser of the terminal 40 is Japanese, and a script 424 showing
 15 <profile>admin</profile> shows that the user of the terminal 40 is an administrator. The scripts 422 through 424 show information based on the terminal type information 63a, the profile information 63b, and the language information 63c of the common path information 60a of the URL.

20 A script 425 showing <deviceName>Printer 1</deviceName> shows that the device name is "Printer 1". A script 426 showing <comment>XXXXXXXXXX</comment> shows that the comment concerning "Printer 1" are "XXXXXXXXXX". A script 427 showing <status>Ready</status> shows that the status of
 25 "Printer 1" is "Ready".

In the first embodiment, the Web page handler 200 includes a function for serializing the process result data provided from the Web page function 300 by describing in XML. Accordingly, each of Web applications 301 of the Web page function 300 is not required to include a processing part for each terminal type.

The style sheet 430, which converts the process result data described in XML to be serialized, into HTML by the XSLT processor 205 based on the terminal type, will be described with reference to FIG.21. FIG.21 is a diagram showing a description example of the style sheet for converting the process result from XML to HTML according to the first embodiment of the present invention.

In the style sheet 430 shown in FIG.21, it is determined by a script 431 whether or not an element sandwiched with <terminal> tags shown by a script 422 of the XML 420 of FIG.20 includes a character string "pda", that is, it is determined whether or not the XML 420 is the process result for the PDA terminal. A style sheet template for the PDA terminal is applied by a script 432 when the character string "pda" is included. Another style sheet template for the general PC is applied when the character string "pda" is not included. The style sheet template for the PDA terminal is described in a script 434, and the style sheet template for the general PC is described in a script 435.

Details of each style sheet template are not shown in FIG. 21.

For example, in a case in that a smaller size of the display screen of the mobile phone 42 or the PDA terminal 43 is concerned, the script 434 may describes the style sheet
5 template for the PDA terminal so that images to display at the client PC 41 are not be displayed, a font size is indicated to be smaller than the PC, or the number of letters is indicated to be less than the PC.

According to the first embodiment, the Web
10 application distribution common library 120 includes a function for converting XML into HTML by XSL. Therefore, it is possible to centralize to create an HTML response corresponding to the terminal type. Therefore, each of Web applications 301 in the Web page function 300 is not required
15 to include processing parts corresponding to various terminal types, respectively.

As described above, XSL for converting XML into HTML is prepared for each of Web applications 301 beforehand. HTML showing the process result corresponding each of Web
20 applications 301 is provided to the terminal 40, and then the process result is displayed at the Web browser of the terminal 40.

When the terminal 40 is the client PC 41, for example, the process result of the function topPage() of the
25 Web default application 310 is described in HTML as shown

in FIG.22. FIG.22 is a diagram showing a description example of HTML for the PC in that the process result of the topPage.cgi is shown, according to the first embodiment of the present invention. In FIG.22, HTML 440 for the PC is
 5 provided to the terminal 40 when the terminal 40 is the client PC 41, and the process result of the function topPage() of the Web default application 310 is displayed at the Web browser of the client PC 41 by a script 441.

A script 442 showing `System`
 10 `Status` shows to display "System Status" by a font size 4. A script 443 showing `` shows to display an image. A script 445 showing `<p>System`
`Name:Printer 1</p>` shows to display "System Name:Printer 1", a script 446 showing `<p>Comment:XXXXXXXXXX</p>` shows to
 15 display "Comment:XXXXXXXXXX", and a script 447 showing `<p>System Status:Ready</p>` shows to display "System Status:Ready".

In accordance with HTML 440 for the PC, the display screen as shown in FIG.23 is displayed at the Web
 20 browser of the client PC 41. FIG.23 is a diagram showing a display example of the system status at the client PC according to the first embodiment of the present invention. In FIG.23, a display screen 450 is formed by three frames by mainFrame.cgi. The header page is displayed by
 25 headerPage.cgi, the menu page is displayed by menuPage.cgi,

and the top page is displayed by topPage.cgi in three frames, respectively.

In the top page, a text 452 showing "System Status" is displayed by the script 442 of HTML 240 of FIG.22, an image 454 is displayed by the script 444 of FIG.22, a text 455 showing "System Name:Printer 1" is displayed by the script 445 of FIG.22, a text 456 showing "Comment:XXXXXXXXXX" is displayed by the script 446 of FIG.22, and a text 457 showing "System Status:Ready" is displayed by the script 447 of FIG.22.

In addition, for example, information as a header is displayed in the frame for displaying the header page. For example, texts 459 showing selectable menu items including "System Status", "Network Settings", "Device Configuration Information", and a like are displayed in the frame for displaying the menu page.

For example, "Network Settings" is described in HTML as `<p>Network Settings</p>`. Since only the relative path information 60b is set in this URL, the common path information 60a is succeeded as it is and information concerning "Network Settings" is displayed in the top page for the PC. That is, a path description from "webNetsettingApl" showing Web application ID is set as the relative path, and a current terminal type information 53a

is succeeded by a description "../". Also, the information concerning "Network Settings" is displayed in the top page for the PC by a description "target="top"".

Similarly, "Device Configuration Information" is described in HTML as "

Device Configuration Information</p>". Accordingly, since only the relative path information 60b is set in this URL, the common path information 60a is succeeded as it is and information concerning "Device Configuration Information" is displayed for the PC.

In a case in that the client PC 41 sends a request to the information processing apparatus 100 according to the present invention, display screen 450 is shown at the client PC 41. However, in a case in that the mobile phone 42 or the PDA terminal 43 sends the same request to the information processing apparatus 100, HTML for the PDA terminal as shown in FIG.24 is created and the display screen as shown in FIG.25 is displayed at the PDA terminal 43, .

FIG.24 is a diagram showing a description example of HTML for the PDA terminal where the process result of topPage.cgi is shown, according to the first embodiment of the present invention. In FIG.24, HTML 440a for the PDA terminal is provided to the terminal 40 when the terminal 40 is the PDA terminal 43, and then the process result of

the function topPage() of the Web default application 310 is displayed at the Web browser of the PDA terminal 43 by a script 441a. A script 442a showing System status shows to display "System Status" by a font size 3. The character font of a script 442a is set smaller for the PDA terminal.

The HTML 440a for the PDA terminal does not include a script corresponding to the script 443 of HTML 440 of the client PC 41.

10 Similar to the scripts 445 and 446 of HTML 440 for the PC, a script 445a showing <p>System Name:Printer 1</p> shows to display "System Name:Printer 1", and a script 446a showing <p>Comment:XXXXXXXXXX</p> shows to display "Comment:XXXXXXXXXX".

15 For the PDA terminal 43 which display area is relatively smaller than the client PC 41, for example, a script 447a corresponding to the script 447 of HTML 440 for the PC displays "Status:Ready", instead of "System Status:Ready", so that the number of letters to display is less than the PC.

20 It is not preferred to divide the display screen into the plurality of display areas for the PDA terminal 43. Therefore, information displayed at other frames at the client PC 41 should be displayed within a single display screen (one page) at the PDA terminal 43. A script 448a is

a script described in HTML for displaying the menu page at the PC, and is described in HTML 440a for the PDA terminal as "<p>Network Settings</p>" and "<p>Device Configuration Information</p>". Therefore, "Network Settings" and "Device Configuration Information" of selectable items displayed in the menu page of the client PC is displayed at the PDA terminal 43. "target="top" is described in HTML 440 for the PC to indicate the frame to display. However, "target="top" is omitted in the script 448a.

A display screen as shown in FIG.25 is displayed at the Web browser of the PDA terminal 43 by HTML 440a for the PDA terminal. FIG.25 is a diagram showing a display example of the system status at the PDA terminal according to the first embodiment of the present invention. In FIG.25, a display screen 450a is formed by a single display screen which is not divided into the plurality of display areas by frames.

A text 452a showing "System Status" is displayed at the display screen 450a by the script 442a of HTML 240a shown in FIG.24. The image displayed at the client PC 41 is not displayed at the PDA terminal 43 and a text 455 showing

"System Name:Printer 1" is displayed by the script 445a. A text 456a showing "Comment:XXXXXXXXXX" is displayed by the script 446a. A text 457a showing "Status:Ready", which number of letters is less than that displayed at the client
5 PC 41, is displayed by the script 447a.

Moreover, "Network Settings" and "Device Configuration Information", which are selectable and displayed in the menu page at the client PC 41 are displayed as a text 458 showing selectable "Network Settings" and
10 "Device Configuration Information" by the script 448a.

In a state in that the display screen 450a is displayed at the mobile phone 42 or the PDA terminal 43, when a user of the PDA terminal 43 selects "Network Settings", the display screen as shown in FIG.26 is displayed at the
15 mobile phone 42 or the PDA terminal 43 since the URL is changed so that the common path information 60a is succeeded and only the relative path information 60b is shown. FIG.26 is a diagram showing a display example of "Network Settings" at the PDA terminal according to the first embodiment of the
20 present invention.

In FIG.26, a display screen 460a is displayed by a page transition from the display screen 450a, and displays a page of "Network Settings" corresponding to the size of the display screen of the mobile phone 42 or the PDA terminal
25 43 since the common path information 60a at the page

transition. The user of the mobile phone 42 or the PDA terminal 43 is not required to conduct a setting to properly display "Network Settings" for the size of the display screen.

5 If the user conduct the page transition (link from one page to another page) with respect to a conventional information processing apparatus that cannot specify the terminal type of the terminal 40, information for the display screen of the client PC 41 is displayed at the mobile phone
10 42 or the PDA terminal 43. As a result, the information is provided unsuitably as shown in FIG.27. Since the terminal type information 53a is not succeeded, letters being too large to read the whole sentence is displayed at the mobile phone 42 or the PDA terminal 43. Therefore, the conventional
15 information processing apparatus cannot provide information suitable for the display screen.

 According to the first embodiment of the present invention, since the HTTP daemon 2 forms the URL so as to call default.cgi when the HTTP daemon 2 receives the first request
20 from the terminal 40, the information processing apparatus 100 can automatically set the URL including the common path information 60a by default.cgi. Therefore, the user of the terminal 40 is not required to input information concerning the display screen of the terminal 40.

25 The common path information 60a is provided prior

to the relative path information 60b in the URL. Thus, a link from one page to another page can be indicated by only the relative path information 60b.

Moreover, the information processing apparatus 5 100 converts the description in XML into the description in HTML based on the terminal type information 53a of the common path information 60a by using a predetermined style sheet. Accordingly, in the information processing apparatus 100, a developer is not required to develop each of the Web 10 applications 301 for each of the terminal types. Therefore, it is possible to reduce workload of the developer. That is, it is possible for the Web applications 301 to output the process result in a unified manner. For example, a development of each of the Web applications 301 is not 15 affected by a different size of the display screen, division of the display screen by the frames, and a like.

According to the first embodiment of the present invention, as the terminal type, the client PC 41 is categorized into "PC", and the mobile phone 42 and the PDA 20 terminal 43 are categorized into "PDA". However, in order to categorize the display screen in detail, various terminal types in addition to "PC" and "PDA" can be applied. Also, various categories can be applied to not only the size of the display screen but also to various characteristics of 25 the display screen.

Also, the present invention can be applied to a case in that the information processing apparatus 100 is connected to a large screen as another terminal 40. That is, as for the large screen, it is possible to change letters to be relatively bigger, to change the number of letters to be more, and a like in order to provide information by an effective display screen. Moreover, it is possible to provide a larger image or a plurality of images for the large screen, so as to effectively provide information.

10 In order to provide information corresponding to the terminal 40, in the information processing apparatus 100, the template corresponding to the terminal type in each style sheet 430 adjusts a display format of the process result provided from the Web page function 300 and additionally
15 provides images to the process result.

As described above, according to the present invention, since the terminal type information 63a is set in the common path information 60a when the request from the terminal 40 is received, even if the page transition is
20 conducted among the plurality of the Web applications 301, the information corresponding to the same terminal type can be always provided at the Web browser of the terminal 40.

Also, a processing part for describing the process result in XML and a processing part for converting
25 XML into HTML are provided separately from the plurality of

Web applications 301 in the Web page function 300.

[Second Embodiment]

An information processing apparatus 1100 will be described according to a second embodiment of the present invention. In the second embodiment according to the present invention, the information processing apparatus 1100 provides the information in a language suitable for a terminal and a user using a terminal connected to the information processing apparatus 1100 through the Internet.

The information processing apparatus 1100 according to the second embodiment includes at least one of a plurality of different image forming functions such as a printer, a FAX, and a copier, and also provides information concerning the image forming functions by a plurality of Web applications. In the second embodiment, for the sake of convenience, a case in that information concerning a copying process and a plotter for conducting a copy will be mainly described.

A hardware configuration of the information processing apparatus 1100 is the same as that of the information processing apparatus 100 shown in FIG.1, and explanation of thereof will be omitted.

FIG.28 is a block diagram showing a functional configuration of the information processing apparatus according to a second embodiment of the present invention.

In FIG.28, the information processing apparatus 1100 is capable of connecting to terminals 1040 including a client PC 1041 for English, a client PC 1042 for Japanese, and a client PC 1043 for Chinese, which have different utilization forms of a language. The information processing apparatus 1100 is a computer to provide information as a response with respect to a request sent from each of the terminals 1040.

The information processing apparatus 1100 mainly includes a network controlling part 1101, a sequence control library 1110, a Web application distribution common library 1120, a Web page handler 1200, a SOAP (Simple Object Access Protocol) library 1201, an XML (eXtensible Markup Language) library 1203, an XSLT (XSL Transformations) processor 1205, a Web page function (WPF) 1300, a printer controlling part 1103, and a scanner controlling part 1105.

The network controlling part 1101 includes at least an HTTP daemon 1002 for conducting a communication control in accordance with an HTTP (Hyper Text Transfer Protocol). The network controlling part 1101 receives the request from each terminal 1040 and provides information as a response with respect to the request.

In order to execute a predetermined process so as to succeed to attribute information showing attributes concerning a utilization form of a Web browser of the terminal 1040 while a user conducts page transitions (browse one Web

page linked from another Web page) among a plurality of Web applications 1301, when the HTTP daemon 1002 receives the request from the terminal 1040, and additionally provides a temporary common path information, and a Web application
5 ID and a CGI (Common Gateway Interface) which are referred to execute the predetermined process, to the URL indicated by the request. Similar to the first embodiment, the HTTP daemon 1002 adds necessary information and creates the URL formed by the common path information 60a and the relative
10 path information 60b as shown in FIG.3. The HTTP daemon 1002 additionally provides predetermined
"/TERMINAL/PROFILE/LANG/webDefaultApl/default.cgi" to the URL.

The sequence control library 1110 is a processing
15 part that is shared with the plurality of Web applications 1301 and handles by a predetermined sequence controlling process a difference between a process sequence of sending and receiving data through the Internet 1016 and another
process sequence of sending and receiving data to/from each
20 of the Web applications 1301.

The Web application distribution common library 1120 is a processing part that is shared with the plurality of Web applications 1301, and that analyzes a request from the terminal 1040 and generates a response for the terminal
25 1040. The Web application distribution common library 1120

converts the response described in XML by the Web page handler 1200 into the response described in a display format by HTML (HyperText Markup Language) corresponding to a Web browser language displayed at each terminal 1040 by using the XSLT processor 1205.

The Web page handler 1200 is a processing part that converts a process language understandable for the Web applications 1301 into another process language understandable in the communication control conducted with the terminal 1040 for the request and the response. The Web page handler 1200 calls one Web application 1301 corresponding to the request via a CGI indicated by the request. Also, the Web page handler 1200 sends a serialization request to the SOAP library 1201 to serialize process result data provided from the Web page function 1300.

The SOAP library 1201 converts the process result data given by variables of C language into a description in XML so as to serialize the process result. In the second embodiment, serialization means to describe the process result provided from the Web page function 1300 in XML.

The XML library 1203 is used by the SOAP library 1201 to serialize the process result by describing in XML. Also, the XML library 1203 is used by the XSLT processor 1205 to generate the process result described in HTML.

The XSLT processor 1205 converts the process

result described in XML into HTML by using the XML library 1203 based on a style sheet 1430 described in XSL (eXtensible Stylesheet Language) corresponding to the Web application 1301 indicated by the request from the terminal 1040. The
5 style sheet 1430 is prepared beforehand by corresponding to each Web application 1301.

A language resource DB 1121 stores each language resource showing a correspondence between the process result from each Web application 1301 and a description in each of
10 languages available by the information processing apparatus 1100. That is, by using the language resource DB 1121, one process result can be described in a plurality of languages. And an available language list 1122 shows a list of languages in which the information processing apparatus 1100 can
15 provide information.

When the Web page function 1300 is called from the Web page handler 1200, for example, inquires the printer controlling part 1103 or the scanner controlling part 1105 mounted to the information processing apparatus 1100 through
20 an API (Application Program Interface) 1017, obtains information showing a status of a plotter 35-1 or a scanner 35-2 (shown in FIG.1), and then provides the information to the Web page handler 1200. Moreover, the Web page function 1300 inquires the network controlling part 1101 through the
25 API 1017, obtains information from the network controlling

part 1101, and provides the information to the Web page handler 1200.

Next, a detailed configuration for executing the Web applications will be described with reference to FIG.29, FIG.30A and FIG.30B. FIG.29 is a block diagram for
5 explaining an execution of the Web applications according to the second embodiment of the present invention. FIG.30A and FIG.30B are diagrams showing hash lists according to the second embodiment of the present invention. In FIG.29, for
10 example, in order to provide information based on the configuration of the URL as shown in FIG.3, the Web page handler 1200 includes a default handler 1210 executed at a first request from the terminal 1040, a system status providing handler 1220 executed by the page transition in
15 accordance with the instruction from the terminal 1040, a system configuration information providing handler 1230 similarly executed by page transition, and a like.

Corresponding to the handlers in the Web page handler 1200, respectively, the Web page function 1300
20 includes the plurality of Web applications 1301: a Web default application 1310, a Web system status providing application 1320, a Web system configuration information providing application 1330, and a like.

Until an initial display screen is displayed at
25 the terminal 1040, the default handler 1210 sequentially

calls the Web default application 1310 through "default.cgi", and then "netsetting.cgi" indicated by the page information 65 in accordance with the format of the URL shown in FIG.3. As a result, for example, network settings of the device such
5 the plotter 35-1 or the scanner 35-2 (shown in FIG.1) mounted in the information processing apparatus 1100 are displayed at the terminal 1040.

The system status providing handler 1220 calls a function for the Web system status providing application
10 1320 for providing information concerning the device mounted in the information processing apparatus 1100. In addition, the system configuration information providing handler 1230 calls the Web system configuration information providing application 1330 so as to obtain a system configuration
15 information of the information processing apparatus 1100 in response to a request from the terminal 1040.

The Web application distribution common library 1120 obtains the Web application ID 64 from a URL, and refers to a hash list 1050a shown in FIG.30A. When the Web application
20 ID 64 shows "webDefaultApl", the Web application distribution common library 1120 executes "default_handler". In the same manner, when the Web application ID 64 shows another Web application ID, the Web application distribution common library 1120 refers to the hash list 1050a, and
25 executes a handler corresponding to the Web application ID

to be executed.

In addition, each of the handlers 1210, 1220, and 1230 in the Web page handler 1200 obtains the page information 65 from the URL, refers to the hash list 1050b shown in FIG.30B, and calls a function corresponding to the page information 65. For example, when the page information 65 shows "default.cgi", "default()" is obtained to call as a function. Similarly, when the page information 65 shows another CGI, each of the handlers 1210, 1220, and 1230 refers to hash list 1050b and obtains a function to call.

Moreover, in order to conduct the XSL conversion request which converts the process result described by XML to the XSLT processor 1205 into HTML, the Web application distribution common library 1120 obtains the page information 65 from the URL specified as a Web page function ID, and obtains a corresponding style sheet 1430 by referring to the hash list 1050b shown in FIG.30B. For example, when the page information 65 shows "netsetting.cgi", the Web application distribution common library 1120 obtains "netsetting.xsl" as a style sheet necessary for the XSL conversion from the hash list 1050b. Similarly, when the page information 65 is another CGI, the Web application distribution common library 1120 obtains a style sheet necessary for the XSL conversion by referring to the hash list 1050b.

In FIG.29, FIG.30A, and FIG.30B, when the page information 65, as the Web page function ID, of the URL is "default.cgi", the function default() is executed, and the Web browser language displayed at the terminal 1040 is determined. Accordingly, the language information of the URL which is temporarily created by the HTTP daemon 1002 is replaced with the determined language and the initial display screen where the URL showing the determined language is set is created.

10 When the page information 65 is "netsetting.cgi", a function netsetting() is executed. For example, the information is generated so as to create a network setting page displaying network settings for a printer as the plotter 35-1.

15 Moreover, when the page information 65 is "sysstatus.cgi", a function sysstatus() is executed so as to generate the information for creating a page displaying a status of the printer as a status of the plotter 35-1. When the page information 65 is "sysconfig.cgi", a function sysconfig() is executed, information showing a system configuration is generated.

25 For the sake of convenience, names of the Web application ID and the Web page handler are unified. But it is not limited to do so since the hash list 1050a corresponds the Web application ID to the Web page handler. Also, names

of the Web page function ID, the function, the style sheet are unified in the same manner. But it is not limited to do so since the hash list 1050b corresponds the Web page function ID, the function, and the style sheet each other.

5 Next, a process flow until information is provided with respect to the first request from the terminal 1040 will be described. FIG.31 and FIG.32 are diagrams showing the process flow for default.cgi according to the second embodiment of the present invention.

10 In FIG.31, the terminal 1040 sends a request additionally providing accept language information by using a GET method of the HTTP (step S111). For example, the terminal 1040 sends the request by indicating a URL "http://AAA".

15 When the information processing apparatus 1100 receives this request, the HTTP daemon 1002 of the information processing apparatus 1100 additionally provides the terminal type information 63a, the profile information 63b, the language information 63c, the Web application ID 20 64, the page information 65 to the URL "http://AAA", and then sends this request to the sequence control library 1110 (step S112). For example, the HTTP daemon 1002 additionally provides "TERMINAL" as the terminal type information 63a, "PROFILE" as the profile information 63b, "LANG" as the 25 language information 63c, "webDefaultApl" as the Web

application ID 64, and "default.cgi" as the page information 65, to the URL "http://AAA", so as to form "http://AAA/TERMINAL/PROFILE/LANG/webDefaultApl/default.cgi".

5 The sequence control library 1110 calls the Web application distribution common library 1120 (step S113). When calling the Web application distribution common library 1120, the sequence control library 1110 sets the HTTP connection information showing information concerning a
10 connection with the terminal 1040, and the hash lists 1050a and 1050b as arguments. In the following, the hash lists 1050a and 1050b are generically called hash lists. That is, the hash lists include the hash lists 150a and 150b and other hash lists. The HTTP connection information uniquely
15 specifies the connection with the terminal 1040 until the connection is disconnected.

 The Web application distribution common library 1120 specifies and calls the default handler 1210 ("default_handler") from the hash list 1050a, as the Web page
20 handler 1200 corresponding to the Web application ID 64 showing "webDefaultApl" based on the URL generated by the HTTP daemon 1002 (step S114).

 In the Web page handler 1200, the default handler 1210 obtains the page information 65 showing "default.cgi"
25 from the URL, and specifies and calls the function default()

from the hash list 1050b as the Web page function 1300 corresponding to "default.cgi" (step S115). In this case, the HTTP connection information is set as the argument. For example, in a case in that the Web page function 1300 is developed by C language, the Web page handler 1200 converts
5 into a process type of C language and then calls the function default().

By executing the function default(), based on the HTTP connection information, language information is
10 analyzed and a URL calling the initial display screen is created by including the common path information 60a determined by the function default () (step S116). A process result data including the URL is returned to the default handler 1210 in the Web page handler 1200 (step S117). In
15 a process by default.cgi, the common path information 60a is determined, and a URL is determined by the common path information 60a and the relative path information 60b for determining a frame configuration of the initial display screen. For example, "/pc/user/en" is determined as the
20 common path information 60a and
"/webDefaultApl/netsetting.cgi" for the network setting page as the initial display screen is determined as the relative path information 60b.

The default handler 1210 sends a serialization
25 request to the SOAP library 1201 in order to describe the

process result data in XML (Step S118). For example, the SOAP library 1201 creates a DOM (Document Object Model) based on the process result data shown by a C language structure, additionally provides necessary elements and attributes (step S119), and describes the process result data in XML by the XML library 1203 (step S120). The process result data described in XML is provided to the default handler 1210 as the serialization result by the SOAP library 1201 (step S121). In the Web page handler 1200, the default handler 1210 provides the serialization result as display data "Response DOM" to display at the terminal 1040, to the Web application distribution common library 1120 (step S122).

In order to convert the display data described in XML into a description of HTML corresponding to the Web browser language displayed at the terminal 1040, the Web application distribution common library 1120 refers to the hash list 1050b, obtains the style sheet "default.xsl" corresponding to the page information 65 showing "default.cgi", and sends the XSL conversion request to the XSLT processor 1205 (step S123). The display data "Response DOM" and the style sheet "default.xsl" are set as arguments for the XSL conversion request.

When the XSLT processor 1205 receives the XSL conversion request, the XSLT processor 1205 executes the style sheet "default.xsl" indicated by the argument.

Accordingly, the XSLT processor 1205 analyzes syntax of the display data "Response DOM" described in XML (parse XML, creates a DOM, additionally provides elements and attributes (step S124), and converts into the description of HTML by
5 using the XML library 1203 (step S125). The XSLT processor 1205 provides the description of HTML to the Web application distribution common library 1120 as a XSL conversion result (step S126).

The process result described in HTML by the Web
10 page function 1300 when the page information 65 shows "default.cgi" is output as a default HTML to the Web application distribution common library 1120. In the default HTML, "netsetting.cgi" is described in HTML to be called. The default HTML is output as a default HTML
15 response.

The default HTML response is sequentially provided from the Web application distribution common library 1120 to the sequence control library 1110 (step S127), and is provided from the sequence control library 1110 to
20 the HTTP daemon 1002 (step S128). After that, the default HTML response is sent as a response with respect to the request of the terminal 1040 in step S111 by the HTTP daemon 1002 (step S129). Then, the process flow for executing the Web default application 1310 by the default.cgi is terminated.
25 In step S117, the common path information 60a is

determined and simply the common path information 60a is added to the relative path information 60b. Accordingly, the Web default application 1310 may describe the process result in HTML and output the process result described in HTML. Thus, steps S118 through S126 may be omitted.

Next, an analyzing process for the language information executed by the function default () in step S116 shown in FIG.31 will be described with reference to FIG.33 and FIG.34 in detail. FIG.33 is a flowchart diagram for explaining the analyzing process for the language information according to the second embodiment of the present invention. FIG.34 is a diagram showing a header information list according to the second embodiment of the present invention.

Similar to the first embodiment, the data structures shown in FIG.9 through FIG.10 and FIG.34 are referred by the analyzing process for the language information shown in FIG.33. Hereinafter, the HTTP connection information 340, the script 346 describing "HTTP_REQUEST_INFO *request", and the script 347 describing "HTTP_RESPONSE_INFO *response" in FIG.9 will be referred as the HTTP connection information 1340, the script 1346, and the script 1347 in the second embodiment. Also, the HTTP request information 350, the remote address 351, the local address 352, the request method 353, the request URL 354,

the HTTP version 355, and the encoded information list 357 in FIG.10 will be referred as the HTTP request information 1350, the remote address 1351, the local address 1352, the request method 1353, the request URL 1354, the HTTP version 5 1355, and the encoded information list 1357.

In the request URL 1354, the URL formed by the common path information 60a and the relative path information 60b as shown in FIG.3 is set by the sequence control library 1110. The HTTP request information 1350 is provided to the 10 Web page handler 1200 and to the Web page function 1300 at the same time of the HTTP connection information 1340. Accordingly, the Web page handler 1200 and the Web applications 1301 share and refer to the common path information 60a.

15 And for example, the header information list 1360 is structured as shown in FIG.34. As shown in FIG.34, the header information list 1360 includes accept language information 1365 showing
 "accept-Language:en-us;ja;q=0.9;ge;q=0.7;it;q=0.6;sp;q=0
 20 .4;pt;q=0.3". The accept language information 1365 indicates the Web browser language displayed at the terminal 1040 with priority. Thus, this script of the accept language information 1365 is analyzed, so as to provide information corresponding to the Web browser language displayed at the
 25 terminal 1040. In the accept language information 1365,

"en-us" indicates US English, "ja" indicates Japanese, "ge" indicates German, "it" indicates Italian, "sp" indicates Spanish, and "pt" indicates Portuguese.

In FIG.33, in response to a call of the function(),
5 the Web default application 1310 obtains the HTTP request information 1350 from the HTTP connection information 1340 (step S101). Moreover, the Web default application 1310 obtains the accept language information 1365 from the HTTP request information 1350 (step S102).

10 Then, the Web default application 1310 obtains the Web browser language from the accept language information 1365 (step S103). Based on the accept language information 1365, languages listed in the accept language information 1365 can be ordered as shown in FIG.35A. That is, as the Web
15 browser language, English is a first language requested from the terminal 1004, Japanese is a second language, German is a third language, Italian is a fourth language, Spanish is a fifth language, Portuguese is a sixth language.

Subsequently, the Web default application 1310
20 obtains available languages to provide for a Web browser of the terminal 1004 (step S104). For example, the available languages are listed with priority in the available language list 1122 in FIG.35B. That is, the information processing apparatus 1100 can provide information in Japanese with a
25 first priority, English with a second priority, German with

a third priority,....

The Web default application 1310 determines whether or not the language request by the user of the terminal 1004 is the available language to provide (step S105). When
5 the language request by the user of the terminal 1004 is not the available language, the Web default application 1310 obtains an operation panel language that is stored in a predetermined storage area 1123 as shown in FIG.35C and used to display information at the operation panel 36 in FIG.1.
10 The Web default application 1310 sets the operation panel language as the language information 63C in the common path information 60a (step S107), and then terminates the analyzing process for the language information.

On the other hand, in step S105, when the language
15 request by the user of the terminal 1004 is the available language, the Web default application 1310 sets the language with higher priority included in both the accept language information 1365 and the available language list 1122 (step S108), and then terminates the analyzing process for the
20 language information.

The default HTML output by default.cgi will be described with reference to FIG.36. FIG.36 is a diagram showing an example of the default HTML output according to the second embodiment of the present invention. In FIG.36,
25 the default HTML 1400 is not displayed at the terminal 1040,

but a script 1401 that is Javascript™ calls the network setting page.

By a script 1402 showing

```
"self.document.cookie="cookieOnOffchecker=on; path="/",
```

5 information concerning the Web browser of the terminal 1040 is obtained. By a scrip 1403 showing

```
"self.location.pathname="/pc/user/en/webDefaultApl/netsetting.cgi", the language information "en" is succeeded, and the Web default application 1310 of the Web page function
```

10 1300 is executed. That is, a network setting HTML is requested. During a series of page transitions conducted by a user after that, an absolute path is indicated by a script 1403 as a reference for a relative path indicated by <a href> tag.

15 FIG.37 and FIG.38 are diagrams showing a process flow by netsetting.cgi according to the second embodiment of the present invention. In FIG.37, the terminal 1040 requests an HTML for displaying the network settings of the plotter 35-1 or the scanner 35-2 mounted to the information
20 processing apparatus 1100 (network setting HTML request) (step S151). The network setting HTML request is conducted by the GET method in which "network setting.cgi" is indicated and the form data is attached.

The HTTP daemon 1002 of the information
25 processing apparatus 1100 sends the HTTP connection

information 1340 and the hash lists to the sequence control library 1110 (step S152). In this case, the HTTP daemon 1002 sets "GET" to the request method of the HTTP request information 1350 related to the HTTP connection information 5 1340, and indicates "netsetting.cgi" to the URL of the request. In addition, the HTTP daemon 1002 sets the form data received from the terminal 1040 to the hash lists.

The sequence control library 1110 calls the Web application distribution common library 1120 (step S153). 10 In this case, the sequence control library 1110 sets the HTTP connection information and the hash lists as arguments.

The Web application distribution common library 1120 specifies and calls the default handler 1210 ("default_handler") from the hash list 1050a as the Web page 15 handler 1200 corresponding to the Web application ID 64 showing "webDefaultApl" based on the URL (step S154).

In the Web page handler 1200, the default handler 1210 obtains the page information 65 showing "netsetting.cgi", and specifies and calls the function 20 netsetting() from the hash list 50b as the Web page function 300 corresponding to "netsetting.cgi" (step S155). In this case, the HTTP connection information 1340 is set as an argument.

For example, in a case in that the Web page 25 function 1300 is developed by C language, the Web page handler

1200 converts into a process type of C language and calls the function netsetting().

By executing the function netsetting(), the Web default application 1310 requests information including a device name, a comment, and a like to the network controlling part 1101 through the API 1017, in order to display the status of a device (for example, plotter 35-1 as the printer) at the initial display screen (netsetting.cgi) (step S156-2). The network controlling part 1101 provides the information including the device name, the comment, and the like in response to the request (step S156-4).

For example, the Web default application 1310 of the Web page function 1300 requests the status of the printer to the printer controlling part 1103 through the API 1017 (printer status request) (step S156-6). The printer controlling part 1103 provides the status of the plotter 35-1 as a printer status to the Web default application 1310 (step S156-8).

Then, the Web default application 1310 provides the printer status, and the terminal type information 63a, the profile information 63b and the language information 63c from the request URL 1354 of the HTTP request information 1350 as the process result data to the default handler 1210 in the Web page handler 1200 (step S157).

In the following, the serialization process for

describing in XML in steps S158, S159, S160, S161, and S162 is the same as the serialization process in steps S118, S119, S120, S121, and S122, and explanation thereof will be omitted.

5 In order to convert the display data described in XML into a description of HTML corresponding to the language displayed at the Web browser of the terminal 1040, the Web application distribution common library 1120 refers to the hash list 1050b, obtains the style sheet

10 "netsetting.xsl" corresponding to the page information 56 showing "netsetting.cgi", and conducts the XSL conversion request with respect to the XSLT processor 1205 (step S163). In this case, the display data "Response DOM" and the style sheet "netsetting.xsl" are set as arguments. When the XSLT

15 processor 1205 receives the XSL conversion request, the XSLT processor 1205 executes the style sheet "netsetting.xsl" indicated in the argument. Accordingly, the XSLT processor 1205 selects one template corresponding to the language from descriptions of the style sheet, analyzes a syntax of the

20 display data "Response DOM" described in XML (parse XML), creates a DOM, additionally provides elements and attributes (step S164), and converts into the description of HTML by using the XML library 1203 (step S165). The language resource DB 1121 is referred by the XSLT processor 1205 to

25 describe the process result in the language displayed at the

browser of the terminal 1004.

XSLT processor 1205 provides the description of HTML as the XSL conversion result to the Web application distribution common library 1120 (step S166).

5 The process result described in HTML by the Web page function 1300 in a case in that the page information 65 is "netsetting.cgi" is output to the Web application distribution common library 1120 as a network setting HTML. Information concerning the network settings of the plotter
10 35-1 is described in the network setting HTML.

This network setting HTML response is provided from the Web application distribution common library 1120 to the sequence control library 1110 (step S167), and then is provided from the sequence control library 1110 to the
15 HTTP daemon 1002 (step S168). Subsequently, the HTTP daemon 1002 sends the network setting HTML response as a response in accordance with HTTP with respect to the request sent from the terminal 1040 in step S151 (step S169). Then, the process flow executed by netsetting.cgi is terminated.

20 As describe above, when the terminal 1040 is the client PC 1041 for English, the network setting HTML is displayed in English at the browser of the client PC 1041. When the terminal 1040 is the client PC 1042 for Japanese, the network setting HTML is displayed in Japanese at the
25 browser of the client PC 1042. In this case in that the

terminal 1040 is the client PC 1043 for Chinese, Chinese is not shown in the available language list 1122. Thus, by steps S106 and S107 of FIG.33, the operation panel language (English) is set as the language information 53c in the common path 60a for the client PC 1043. Accordingly, the network setting HTML is displayed in English at the browser of the client PC 1043.

The process result described in XML will be described. FIG.39 is a diagram showing an example of the process result described in XML by netsetting.cgi according to the second embodiment of the present invention.

In an XML 1500 shown in FIG.39, the process result by the function netsetting() of the Web default application 1310 is shown by a script 1501 showing from <networkResponse> to </networkResponse>. A script 1502 showing <terminal>pc</terminal> shows that the terminal 1040 is a personal computer, a script 1503 showing <language>en</language> shows that a language displayed at the Web browser of the terminal 1040 is English, and a script 1504 showing <profile>user</profile> shows that the user of the terminal 1040 is a regular user. The scripts 1502 through 1504 show information based on the terminal type information 63a, the profile information 63b, and the language information 63c of the common path information 60a of the URL.

A script 1505 showing

`<returnValue>SUCCESS</deviceName>` shows that the network settings are successfully conducted. A script 1506 showing `<ipAddress>999.999.999.999</ipAddress>` shows that the IP address of the device (for example, the plotter 35-1) is "999.999.999.999". A script 1507 showing `<subnetMask>255.255.255.0</subnetMask>` shows that the subnet mask is "255.255.255.0". A script 1508 showing `<hostName>Printer 1</hostname>` shows that the name of the device is "Printer 1".

In the second embodiment, the Web page handler 1200 includes a function for serializing the process result data provided from the Web page function 1300 by describing in XML. Accordingly, each of Web applications 1301 of the Web page function 1300 is not required to include a processing part for describing the process result in each language.

A language resource, which is managed in the language resource DB 1121 and used to convert the process result described in XML into a description in HTML capable of showing the process result in English, will be described with reference to FIG.40. FIG.40 is a diagram showing an example of the language resource according to the second invention of the present invention.

A script 1591 showing `<?xml:lang='en'>` shows English by a parameter "lang" indicating "en". That is, the

language resource 1590 is used for English. Scripts 1592 through 1595 are referred to correspond the process result to descriptions in English. In script 1592, "NETSETTING" indicated by a parameter "key" corresponds to "Network Settings" indicated by a parameter "text". In script 1593, "IP_HOSTNAME" indicated by the parameter "key" corresponds to "Host Name" indicated by the parameter "text". In script 1594, "IP_ADDRESS" indicated by the parameter "key" corresponds to "IP Address" indicated by the parameter "text". In script 1595, "IP_SUBNET" indicated by the parameter "key" corresponds to "Subnet Mask" indicated by the parameter "text".

The style sheet 1430 for converting the process result form netsetting.cgi described in XML into HTML based on the language resource 1590 will be described with reference to FIG.41 through FIG.43. FIG.41 through FIG.43 are diagrams showing a description example of the style sheet for converting the process result from XML to HTML according to the second embodiment of the present invention.

In the style sheet 1430 shown in FIG.41, for example, a script 1433 selects the language resource 1590 and the language resource 1590 is referred to convert XML into HTML. In this case, the language resource 1590 is indicated as an argument \$langTable of a function document().

A script 1435 showing <xsl:output method="html"

encoding="UTF-8"/> indicates to describe the process result in HTML. Moreover, a structure of the HTML is defined by scripts 1417 and 1418. In this case, the script 1437 indicates a language as an attribute, and the script 1438
 5 applies the template to describe a body of the HTML.

Furthermore, the style sheet 1430 is partially shown in FIG.42 and FIG.43 to generate the body of the HTML. A script 1441 showing <xsl:template match="networkResponse"> indicates "networkResponse" by a
 10 parameter "match", that is, the script 1441 indicates a template for netsetting.cgi. And the language resource 1590 in FIG.40 is referred and then "NETSETTING" corresponds to the "Network Settings" as a title of the Web page by a script 1443. Similar to the script 1443, "IP_HOSTNAME" corresponds
 15 to "Host Name", "IP_ADDRESS" corresponds to "IP Address", and a like.

A template named as "staticValue" is described from a script 1451 to a script 1460, and is used in the script 1445 of FIG.42. Another template named as "sf:StringHndler"
 20 is described from a script 1471 to a script 1480, and is used in the script 1443 of FIG.42.

As described above, the XSLT processor 1205 converts the process result described in XML into HTML based on the style sheet 1430 and the language resource 1590.
 25 Therefore, a creation of the network setting HTML for each

language can be centralized in the XSLT processor 1205. Therefore, each of the Web applications 1301 in the Web page function 1300 is not required to have a function for creating a description in HTML for each language.

5 By preparing the style sheet 1430 for each of the Web applications 1301 beforehand, the process result can be properly described in a suitable language for the Web browser of the terminal 1040.

10 The network setting HTML showing the process result by netsetting.cgi is described as shown in FIG.44. FIG.44 is a diagram showing an example of the network setting HTML in English showing the process result of netsetting.cgi, according to the second embodiment of the present invention. In a network setting HTML 1570 shown in FIG.44, a script 1571
15 showing `<meta http-equiv="Content-Language" content="en">` shows that the process result is provided in English. Scripts 1573 and 1575 are created based on the style sheet 1430 to display in English at the browser of the terminal 1040. The script 1575 is to link to one of other Web pages.

20 By the script 1575, the network setting HTML can be linked to either one of two Web pages: "Browse System Status" page and "Browse System Configurations". By a script 1576 showing `>a href="../../../webSysstatusApl/sysstatus.cgi">`, "webSysstatusApl" as the Web application information 64 and
25 "sysstatus.cgi" as the page information 65 are set as the

relative path. When the "Browse System Status" page is selected by the user of the terminal 1040, the "Browse System Status" page is displayed at the terminal 1040 while a current language information 63c is succeeded to by "../". In the same manner, By a script 1577 showing , "webSysconfigApl" as the Web application information 64 and "sysconfig.cgi" as the page information 65 are set as the relative path. When the "Browse System Configurations" page is selected by the user of the terminal 1040, the "Browse System Configurations" page is displayed at the terminal 1040 while a current language information 63c is succeeded to by "../".

The network setting page is displayed in English as shown in FIG.45 by the network setting HTML in FIG.44. FIG.45 is a diagram showing the network setting page displayed in English according to the second embodiment of the present invention. In a network setting page 1580 shown in FIG.45, an English display 1583 and an English selectable display 1585 are displayed at the terminal 1040 when the terminal 1040 is the client PC 1041 for English. The English display 1583 is displayed based on the script 1573 in FIG.44. The English selectable display 1585 is displayed based on the script 1575 in FIG.44.

When the user of the client PC 1041 clicks "Browse

system status" from the English selectable display 1585, another Web page is displayed in English at the browser of the client PC 1041 for English as shown in FIG.46.

FIG.46 is a diagram showing another Web page
5 linked from the network setting page in FIG.45 according to the second embodiment of the present invention. In FIG.46, a system status page 1790 corresponding to "Browse system status" in the English selectable display 1585 of FIG.45 is displayed in English at the client PC 1041. When the user
10 of the client PC 1041 selects "Japanese" from a language list 1795 and clicks a GO button 1796, a system status HTML showing the process result from sysstatus.cgi is created in the information processing apparatus 1100 as shown in FIG.47.

FIG.47 is a diagram showing an example of the
15 system status HTML in Japanese showing the process result of sysstatus.cgi, according to the second embodiment of the present invention. In a system status HTML 1670 shown in FIG.47, a script 1671 showing <meta
http-equiv="Content-Language" content="ja"> shows that the
20 process result is provided in Japanese. A script 1673 is created based on a style sheet other than the style sheet 1430 to display information concerning the process result in Japanese at the browser of the terminal 1041 for English. A script 1674 is created based on the same style sheet for
25 the script 1673 to display a selectable list for selecting

one language in Japanese. A script 1675 is to link to one of other Web pages.

Based on the system status HTML 1670, the system status page 1790 in English is changed to display in Japanese as shown in FIG.48. FIG.48 is a diagram showing an example of a system status page in Japanese according to the second embodiment of the present invention. In FIG.48, a system status page 1690 is displayed in Japanese after the user selects "Japanese" at the system status page 1790 in FIG.46, and then the process result of sysstatus.cgi is displayed in Japanese. In a case in which the user selects one Web page from a selectable display 1697, "Japanese" is succeeded as the language information 53c in the common path information 60.

Accordingly to the second embodiment of the present invention, since the HTTP daemon 1002 forms the URL so as to call default.cgi when the HTTP daemon 1002 receives the first request from the terminal 1040, the information processing apparatus 1100 can automatically set the URL including the common path information 60a by default.cgi. Therefore, the user of the terminal 1040 is not required to input information concerning the language displayed at the browser of the terminal 1040.

The common path information 60a is provided prior to the relative path information 60b in the URL. Thus, a link

from one page to another page can be indicated by only the relative path information 60b.

Moreover, the information processing apparatus 1100 converts the description in XML into the description in HTML based on the language information 53c of the common path information 60a by using a predetermined style sheet. Accordingly, in the information processing apparatus 1100, a developer is not required to develop each of the Web applications 1301 for each of the languages. Therefore, it is possible to reduce workload of the developer. That is, it is possible for the Web applications 1301 to output the process result in a unified manner. For example, a development of each of the Web applications 1301 is not affected by the plurality of languages.

As described above, according to the present invention, since the language information 63c is set in the common path information 60a when the request from the terminal 1040 is received, even if the page transition is conducted among the plurality of the Web applications 1301, the information corresponding to the same language can be always provided at the Web browser of the terminal 1040.

Also, a processing part for describing the process result in XML and a processing part for converting XML into HTML are provided separately from the plurality of Web applications 1301 in the Web page function 1300.

[Third Embodiment]

An information processing apparatus 2100 will be described according to a third embodiment of the present invention. In the third embodiment according to the present invention, the information processing apparatus 2100 provides the process result suitable for a profile of the user connected to the information processing apparatus 2100 through the Internet.

The information processing apparatus 2100 according to the third embodiment includes at least one of a plurality of different image forming functions such as a printer, a FAX, and a copier, and also provides information concerning the image forming functions by a plurality of Web applications. In the third embodiment, for the sake of convenience, a case in that information concerning a copying process and a plotter for conducting a copy will be mainly described.

A hardware configuration of the information processing apparatus 2100 is the same as that of the information processing apparatus 100 shown in FIG.1, and explanation of thereof will be omitted.

FIG.49 is a block diagram showing a functional configuration of the information processing apparatus according to the third embodiment of the present invention. In FIG.49, the information processing apparatus 2100 is

capable of connecting to terminals 2040 including a client PC 2041 used by a regular user, a client PC 2042 used by a system administrator, and a client PC 2043 used by another regular user, which require to display information
5 corresponding to a profile. The information processing apparatus 2100 is a computer to provide information as a response with respect to a request sent from each of the terminals 2040.

The information processing apparatus 2100 mainly
10 includes a network controlling part 2101, a sequence control library 2110, a Web application distribution common library 2120, a Web page handler 2200, a SOAP (Simple Object Access Protocol) library 2201, an XML (eXtensible Markup Language) library 2203, an XSLT (XSL Transformations) processor 2205,
15 a Web page function (WPF) 2300, a printer controlling part 2103, and a scanner controlling part 2105.

The network controlling part 2101 includes at least an HTTP daemon 2002 for conducting a communication control in accordance with an HTTP (Hyper Text Transfer
20 Protocol). The network controlling part 2101 receives the request from each terminal 2040 and provides information as a response with respect to the request.

In order to execute a predetermined process so as to succeed to attribute information showing attributes
25 concerning a utilization form of a Web browser of the terminal

2040 while a user conducts page transitions (browse one Web page linked from another Web page) among a plurality of Web applications 2301, when the HTTP daemon 2002 receives the request from the terminal 2040, and additionally provides
5 a temporary common path information, and a Web application ID and a CGI (Common Gateway Interface) which are referred to execute the predetermined process, to the URL indicated by the request. Similar to the first embodiment, the HTTP daemon 2002 adds necessary information and creates the URL
10 formed by the common path information 60a and the relative path information 60b as shown in FIG.3. The HTTP daemon 2002 additionally provides predetermined
"/TERMINAL/PROFILE/LANG/webDefaultApl/default.cgi" to the URL.

15 The sequence control library 2110 is a processing part that is shared with the plurality of Web applications 2301 and handles by a predetermined sequence controlling process a difference between a process sequence of sending and receiving data through the Internet 2016 and another
20 process sequence of sending and receiving data to/from each of the Web applications 2301.

The Web application distribution common library 2120 is a processing part that is shared with the plurality of Web applications 2301, and that analyzes a request from
25 the terminal 2040 and generates a response for the terminal

2040. The Web application distribution common library 2120 converts the response described in XML by the Web page handler 2200 into the response described in a display format by HTML (HyperText Markup Language) corresponding to the profile of the user using each terminal 2040 by using the XSLT processor 2205.

The Web page handler 2200 is a processing part that converts a process language understandable for the Web applications 2301 into another process language understandable in the communication control conducted with the terminal 2040 for the request and the response. The Web page handler 2200 calls one Web application 2301 corresponding to the request via a CGI indicated by the request. Also, the Web page handler 2200 sends a serialization request to the SOAP library 2201 to serialize process result data provided from the Web page function 2300.

Moreover, in the third embodiment, the Web page handler 2200 conducts an authenticating process for the user of the terminal 2040 by referring to an authentication information DB 2121. When the user is authenticated, the process result provided from the Web page function 2300 is provided based on the profile of the user. The profile is a category of the user and shows an authorization level such as a regular user, a system administrator, a service person, and a like. For example, the user categorized as

"administrator" is allowed to change network settings related to devices such as the plotter 35-1 or the scanner 35-2 (shown in FIG.1). The user categorized as "regular user" is only allowed to display the network settings or
5 cannot access information related to the network settings. The profile is used to determine a method for providing information.

The authentication information DB 2121 manages a user name, a user password, a registered profile, and a
10 like for each user. The registered profile shows the profile of the user when the user is registered.

The SOAP library 2201 converts the process result data given by variables of C language into a description in XML so as to serialize the process result. In the third
15 embodiment, serialization means to describe the process result provided from the Web page function 2300 in XML.

The XML library 2203 is used by the SOAP library 2201 to serialize the process result by describing in XML. Also, the XML library 2203 is used by the XSLT processor 2205
20 to generate the process result described in HTML.

The XSLT processor 2205 converts the process result described in XML into HTML by using the XML library 2203 based on a style sheet 2430 described in XSL (eXtensible Stylesheet Language) corresponding to the Web application
25 2301 indicated by the request from the terminal 2040. The

style sheet 2430 is prepared beforehand by corresponding to each Web application 2301.

When the Web page function 2300 is called from the Web page handler 2200, for example, inquires the printer
5 controlling part 2103 or the scanner controlling part 2105 mounted to the information processing apparatus 2100 through an API (Application Program Interface) 2017, obtains information showing a status of a plotter 35-1 or a scanner 35-2 (shown in FIG.1), and then provides the information to
10 the Web page handler 2200. Moreover, the Web page function 2300 inquires the network controlling part 2101 through the API 2017, obtains information from the network controlling part 2101, and provides the information to the Web page handler 2200.

15 Next, a detailed configuration for executing the Web applications 2301 will be described with reference to FIG.50. FIG.50 is a block diagram for explaining an execution of the Web applications according to the third embodiment of the present invention. In FIG.50, for example,
20 in order to provide information based on the configuration of the URL as shown in FIG.3, the Web page handler 2200 includes an authentication handler 2205 executed to authenticate the user of the terminal 2040, a default handler 2210 executed at a first request from the terminal 2040 and
25 at a role change request for requesting the Web page suitable

for a higher profile like the administrator, a system status providing handler 2220 executed by the page transition in accordance with the instruction from the terminal 2040, a system configuration information providing handler 2230
5 similarly executed by page transition, and a like.

Until an initial display screen is displayed at the terminal 2040, the default handler 2210 sequentially calls the Web default application 2310 through "default.cgi", and then "netsetting.cgi" indicated by the page information
10 65 in accordance with the format of the URL shown in FIG.3. As a result, for example, network settings of the device such the plotter 35-1 or the scanner 35-2 (shown in FIG.1) mounted in the information processing apparatus 2100 are displayed at the terminal 2040.

15 The system status providing handler 2220 calls a function for the Web system status providing application 2320 for providing information concerning the device mounted in the information processing apparatus 2100. In addition, the system configuration information providing handler 2230
20 calls the Web system configuration information providing application 2330 so as to obtain a system configuration information of the information processing apparatus 2100 in response to a request from the terminal 2040.

In the same manner of the second embodiment, the
25 Web application distribution common library 2120 executes

each of the handlers 2210 through 2230 based on the Web information ID 64 of the URL shown in FIG.3 by referring the hash lists 1050a shown in FIG.30A, and each of the handlers 2210 through 2230 executes the Web applications 2301 based
5 on the page information 65 of the URL shown in FIG.3 by referring the hash list 1050b shown in FIG.30B. Also, in order to conduct the XSL conversion request which converts the process result described by XML to the XSLT processor 2205 into HTML, the Web application distribution common
10 library 2120 selects the style sheet 2430 based on the page information 65 of the URL by referring to the hash list 1050b shown in FIG.30B. Therefore, detailed explanation thereof will be omitted.

In the third embodiment, When the Web default
15 application 2310 is executed through "rolechange.cgi", the Web default application 2310 replaces the profile information 63b in the common path information 60a of the URL with the profile as the regular user. In this case, the default handler 2210 calls a function rolechange() based on
20 "rolechange.cgi". The Web application distribution common library 2120 selects the style sheet 2430 based on the page information 65 showing "rolechange.cgi". For example, the style sheet 2430 is properly selected by "rolechange.xsl" corresponding "rolechange.cgi". The Web application
25 distribution common library 2120 executes the authentication

handler 2205 by "authentication_handler" to authenticate the user of the terminal 2040 when the user requests the Web page for the higher profile.

For example, when the user who is actually the
5 system administrator of the terminal 2042 accesses the information processing apparatus 2100 as the regular user to display the initial display screen, in accordance with the process flows shown in FIGS.31, 32, 37, and 38 similar to the second embodiment, the default handler 2210
10 sequentially calls the Web default application 2310 through "default.cgi", and then "netsetting.cgi" to display the initial display screen at the terminal 2042, as described above. As a result, for example, the network setting page are displayed at the terminal 2042 as shown in FIG.45 in the
15 second embodiment.

The network setting page in FIG.45 in the second embodiment is the Web page for the regular user. Thus, the network setting page in FIG.45 shows information concerning the network settings but the user of the terminal 2042 is
20 not allowed to set or change the network settings. Since the user of the terminal 2042 is the administrator, the user requests the network setting page for the system administrator to the information processing apparatus 2100. That is, the user requests the network setting page for the
25 higher profile.

A process flow to change the Web browser corresponding to a desired profile of the user will be described with reference to FIG.51 through FIG.53.

FIG.51 is a diagram showing a process flow by
5 rolechange.cgi according to the third embodiment of the present invention. In FIG.51, the user of the terminal 2042 selects the network setting page for the system administrator from a menu showing a profile lists. In this case, a menu HTML for displaying the menu includes a script for each
10 profile. For example,
 is described for the system administrator in the menu HTML. This script indicates that "rolechange.cgi" changes the profile information 53b in a current common path information
15 60a to "admin" showing the system administrator.

When the user selects the network setting page for the system administrator, an HTML request changing a role is sent from the terminal 2042 to the information processing apparatus 2100 by indicating a URL of
20 "/pc/admin/en/webDefaultApl/rolechange.cgi" (step S231).

Based on "webDefaultApl/rolechange.cgi", the default handler 2210 calls the function rolechange() so that the Web default application 2310 is executed. Then, the Web default application 2310 in the Web page handler 2300 obtains
25 profile information 53b from the common path information 60a

of the URL and creates a URL to call the network setting page having the profile information 53b showing "admin" (step S235). For example, "/pc/admin/en" is determined as the common path information 60a and

5 "/webDefaultApl/netsetting.cgi" is determined as the relative path information 60b. And the XSLT processor 2205 generates an HTML response having the URL calling the network setting page for the system administrator based on "rolechange.xsl". The HTML response is sent to the terminal
10 2042.

The HTML is not display at the browser of the terminal 2042 but automatically calls a HTML request displaying network settings with the profile information 53b showing "admin" (step S240).

15 The authentication handler 2205 includes an authentication determining part 2206 for determining whether or not the user is required to be authenticated based on the URL of the HTML request and an authenticating part 2208 for authenticating the user by referring the authentication
20 information DB 2121. When the authentication handler 2205 is executed, the authentication handler 2208 obtains the profile information 53b set in the URL and the determining part 2206 determines whether or not the profile information 53b shows "admin" (step S243).

25 In this case, since the profile information 53b

shows "admin", the determining part 2206 determines that the user is required to be authenticated. Thus, the authentication handler 2205 sends an authentication request, that is, sends a predetermined "401 error" to require
5 authentication information to the terminal 2042 (step S245). On the other hand, when the determining part 2206 determines that the user is not required to be authenticated, the authenticating part 2208 of the authentication handler 2205 executes the Web default application 2310 by calling the
10 function "netsetting.cgi" (step S244).

The terminal 2042 displays a password input screen to prompt the user to input the password of the user and sends an authentication response showing authentication information including the password input by the user to the
15 information processing apparatus 2100 (step S250). Generally, a regular Web browser implements this authentication process sequence. It is not limited to this authentication process sequence but a special authentication screen can be formed and an original authentication process
20 can be conducted.

The authenticating part 2208 of the authentication handler 2205 conducts the authentication process to authenticate the user based on the password input by the user by referring the authentication information DB
25 2121. When the user is successfully authenticated, the

authentication handler 2205 executes the default application 2310 through "netsetting.cgi" (step S255).

After the process result is provided from the default application 2310, the network setting HTML for the system administrator is created based on the profile information 53c showing "admin" and sent to the terminal 2042.

Once the terminal 2042 accesses the information processing apparatus 2100 by the URL of
10 "/pc/admin/en/webDefaultApl/rolechange.cgi",
"/pc/admin/en" is always succeeded while the user conducts the page transition. After that, the Web page provided from the information processing apparatus 2100 by the page transition can be the Web page for the system administrator.

15 Next, a process flow conducted by netsetting.cgi from step S255 and step S270 will be described with reference to FIG.52 and FIG.53 in detail. FIG.52 and FIG.53 are diagrams showing the process flow by netsetting.cgi according to the third embodiment of the present invention.
20 In FIG.52, the default handler 2210 of the Web page handler 2200 obtains the page information 65 showing "netsetting.cgi", and specifies and calls the function netsetting() corresponding to "netsetting.cgi" (step S255). In this case, the HTTP connection information 2340 is set
25 as an argument.

For example, in a case in that the Web page function 2300 is developed by C language, the Web page handler 2200 converts into a process type of C language and calls the function netsetting().

5 By executing the function netsetting(), the Web default application 2310 requests information including a device name, a comment, and a like to the network controlling part 2101 through the API 2017, in order to display the status of a device (for example, plotter 35-1 as the printer) at
10 the initial display screen (netsetting.cgi) (step S256-2). The network controlling part 2101 provides the information including the device name, the comment, and the like in response to the request (step S256-4).

For example, the Web default application 2310 of
15 the Web page function 2300 requests the status of the printer to the printer controlling part 2103 through the API 2017 (printer status request) (step S256-6). The printer controlling part 2103 provides the status of the plotter 35-1 as a printer status to the Web default application 2310 (step
20 S256-8).

Then, the Web default application 2310 provides the printer status, and the terminal type information 63a, the profile information 63b and the language information 63c from the request URL 2354 of the HTTP request information
25 2350 as the process result data to the default handler 2210

in the Web page handler 2200 (step S257).

In the following, the serialization process for describing in XML in steps S258, S259, S260, S261, and S262 is the same as the serialization process in steps S118, S119, 5 S120, S121, and S122 in the second embodiment, and explanation thereof will be omitted.

In order to convert the display data described in XML into a description of HTML corresponding to the profile of the user using the terminal 2042, the Web application 10 distribution common library 2120 obtains the style sheet "netsetting.xsl" corresponding to the page information 56 showing "netsetting.cgi", and conducts the XSL conversion request with respect to the XSLT processor 2205 (step S263). In this case, the display data "Response DOM" and the style 15 sheet "netsetting.xsl" are set as arguments. When the XSLT processor 2205 receives the XSL conversion request, the XSLT processor 2205 executes the style sheet "netsetting.xsl" indicated in the argument. Accordingly, the XSLT processor 2205 selects one template corresponding to the profile from 20 descriptions of the style sheet, analyzes a syntax of the display data "Response DOM" described in XML (parse XML), creates a DOM, additionally provides elements and attributes (step S264), and converts into the description of HTML by using the XML library 2203 (step S265).

25 XSLT processor 2205 provides the description of

HTML as the XSL conversion result to the Web application distribution common library 2120 (step S266) .

The process result described in HTML by the Web page function 2300 in a case in that the page information
5 65 is "netsetting.cgi" is output to the Web application distribution common library 2120 as a network setting HTML. Information concerning the network settings of the plotter 35-1 is described in the network setting HTML.

This network setting HTML response is provided
10 from the Web application distribution common library 2120 to the sequence control library 2110 (step S267) , and then is provided from the sequence control library 2110 to the HTTP daemon 2002 (step S268) . Subsequently, the HTTP daemon 2002 sends the network setting HTML response as a response
15 in accordance with HTTP with respect to the request sent from the terminal 2042 (step S269) . Then, the process flow executed by "netsetting.cgi" is terminated.

Values that can be set in the URL as the profile information 53b will be describe with reference to FIG.54.
20 FIG.54 is a diagram showing a correspondence between the profile information to set in the URL and the profile of the user according to the third embodiment of the present invention. In FIG.54, "user" set in the URL shows that the user requests the Web page as the regular user, "admin" set
25 in the URL shows that the user requests the Web page as the

system administrator, "service" shows that the user requests the Web page as the service person, and a like.

The authentication handler 2205 may send "401 error" if the profile information 53c set in the URL is higher level than the profile of the user managed in the authentication information DB 2121. The authentication handler 2205 may determine whether or not the user is required to be authenticated.

FIG.55 is a diagram showing an example of the HTML response calling the network setting page for the system administrator according to the third embodiment of the present invention. In FIG.55, an HTML response 2400 is not displayed at the terminal 2042, but a script 2401 that is Javascript™ calls the network setting page.

By a script 2402 showing
"self.document.cookie="cookieOnOffchecker=on; path=/"", information concerning the Web browser of the terminal 2042 is obtained. By a scrip 2403 showing
"self.location.pathname="/pc/admin/en/webDefaultApl/nets
etting.cgi"", the profile information "admin" is succeeded, and the Web default application 2310 of the Web page function 2300 is executed. That is, a network setting HTML for the system administrator is requested. During a series of page transitions conducted by the user after that, an absolute path is indicated by a script 2403 as a reference for a

relative path indicated by <a href> tag.

The process result described in XML will be described. FIG.56 is a diagram showing an example of the process result described in XML by netsetting.cgi according to the third embodiment of the present invention.

In FIG.56, an XML 2500 shows the process result when the user is successfully authenticated to change the profile information 53c from "user " to "admin". In an XML 2500 shown in FIG.56, the process result by the function netsetting() of the Web default application 2310 is shown by a script 2501 showing from <networkResponse> to </networkResponse>. A script 2502 showing <terminal>pc</terminal> shows that the terminal 2042 is a personal computer, a script 2503 showing <language>en</language> shows that a language displayed at the Web browser of the terminal 2042 is English, and a script 2504 showing <profile>admin</profile> shows that the user of the terminal 2042 is the system administrator. The scripts 2502 through 2504 show information based on the terminal type information 63a, the profile information 63b, and the language information 63c of the common path information 60a of the URL.

A script 2505 showing <returnValue>SUCCESS</returnValue> shows that the network settings are successfully conducted. A script 2506 showing

`<ipAddress>999.999.999.999</ipAddress>` shows that the IP address of the device (for example, the plotter 35-1) is "999.999.999.999". A script 2507 showing
`<subnetMask>255.255.255.0</subnetMask>` shows that the
5 subnet mask is "255.255.255.0". A script 2508 showing
`<hostName>Printer 1</hostname>` shows that the name of the device is "Printer 1".

In the third embodiment, the Web page handler 2200 includes a function for serializing the process result
10 data provided from the Web page function 2300 by describing in XML. Accordingly, each of Web applications 2301 of the Web page function 2300 is not required to include a processing part for describing the process result for each profile.

The style sheet 2430, which converts the process
15 result data described in XML to be serialized, into HTML by the XSLT processor 2205 based on the terminal type, will be described with reference to FIG.57. FIG.57 is a diagram showing a description example of the style sheet for converting the process result from XML to HTML according to
20 the third embodiment of the present invention.

In the style sheet 2430 shown in FIG.57, it is determined by a script 2431 whether or not an element sandwiched with `<terminal>` tags shown by a script 2504 of the XML 2500 of FIG.56 includes a character string "admin",
25 that is, it is determined whether or not the XML 2500 is the

process result for the system administrator. A style sheet template for the system administrator is applied by a script 2432 when the character string "admin" is included. Another style sheet template for the regular user is applied when
5 the character string "admin" is not included. The style sheet template for the system manager is described in a script 2434, and the style sheet template for the regular user is described in a script 2435. Details of each style sheet template are not shown in FIG.57.

10 When the terminal 2042 requests the network setting page for the system administrator, for example, the process result of the function netsetting() of the Web default application 2310 is described in HTML as shown in FIG.58. FIG.58 is a diagram showing a description example
15 of HTML for the system administrator in that the process result of the netsetting.cgi is shown, according to the third embodiment of the present invention. In FIG.58, HTML 2570 for the system administrator is provided to the terminal 2042 when the terminal 2042 requests the network setting page for
20 the system administrator and the user is authenticated as the system administrator, and the process result of the function netsetting() of the Web default application 2310 is displayed at the Web browser of the terminal 2042 by scripts 2573 and 2575.

25 The 2573 and 2575 are created based on the style

sheet 2430 to display for the system administrator at the browser of the terminal 2042. The script 2573 is a script described in HTML for allowing the user input information concerning the network settings and send the information
5 input by the user to the information processing apparatus 2100. The script 2575 is to link to one of other Web pages.

By the script 2575, the network setting HTML can be linked to either one of two Web pages: "Browse System Status" page and "Browse System Configurations". By a script
10 2576 showing `>a href="../../../webSysstatusApl/sysstatus.cgi">`, "webSysstatusApl" as the Web application information 64 and "sysstatus.cgi" as the page information 65 are set as the relative path. When the "Browse System Status" page is selected by the user of the terminal 2042, the "Browse System
15 Status" page is displayed at the terminal 2042 while a current language information 63c is succeeded to by "../../../". In the same manner, By a script 2577 showing ``, "webSysconfigApl" as the Web application information 64 and
20 "sysconfig.cgi" as the page information 65 are set as the relative path. When the "Browse System Configurations" page is selected by the user of the terminal 2042, the "Browse System Configurations" page is displayed at the terminal 2042 while a current profile information 63b is succeeded to by
25 "../../../".

The network setting page is displayed in English as shown in FIG.59 by the network setting HTML in FIG.58. FIG.59 is a diagram showing the network setting page for the system administrator according to the third embodiment of the present invention. In a network setting page 2580 shown in FIG.59, an input area 2584 and a selectable display 2585 are displayed at the terminal 2042 when the user of the terminal 2042 is successfully authenticated as the system administrator. The input area 2584 is displayed based on the script 2573 in FIG.58. The selectable display 2585 is displayed based on the script 2575 in FIG.58.

As described above, when the user conducts the page transition among the Web applications 2301, the profile information 53c is automatically succeeded. Therefore, the user of the terminal 2040 is not required to indicate the profile of the user to request the Web page suitable for the profile.

Moreover, in the information processing apparatus 2100, a consistency of creating the web page suitable for the profile of the user can be maintained among the Web applications 2301 in the Web page function 2300. In addition, each of the Web applications 2301 is not required to include a process for creating the Web page for each profile.

Furthermore, the profile information 53c is

succeeded with respect to the request from each of the terminals 2040. Therefore, it is possible to display the Web page suitable for the profile of the user at the terminal 2040. In addition, the user is authenticated when the user
5 changes the profile to display the Web page suitable for the profile. Accordingly, it is possible to protect information maintained in the information processing apparatus 2100 depending on the profile of the user.

The present invention is not limited to the
10 specifically disclosed embodiments, and variations and modifications may be made without departing from the scope of the present invention.

The present application is based on the Japanese priority applications No.2002-212300 filed on July 22, 2002,
15 No.2002-242548 filed on August 22, 2002, No.2002-242550 filed on August 22, 2002, and No.2003-197850 filed on July 16, 2003 the entire contents of which are hereby incorporated by reference.